



## Safety light curtain

### SLCT14



- Resolution 14 mm (finger protection)
- Protection field height up to 1200 mm
- Self-testing (type 2 as per IEC/EN 61496-1)
- SIL1 acc. to IEC 61508
- Degree of protection IP67
- Temperature range -35 ... 60°C (-31 ... 140 °F)
- Slim design, mounting on three sides

### Safety light curtain




### Function

The safety light curtain consists of a transmitter and a receiver unit. The protected area is formed by infrared light beams transmitted from the transmitter unit to the receiver unit. The spacing between the individual light beams determines the minimum obstruction size (14 mm) that can be reliably detected within the entire protected area range.

### Application

- Active opto-electronic protective device (AOPD) for protection of people in danger zones and high risk areas
- Hand protection from 30 mm resolution
- Finger protection from 14 mm resolution

Dimensions



Technical Data

| General specifications               |   |
|--------------------------------------|---|
| Effective detection range            | 0.2 ... 8 m   |
| Light source                         | IREC  |
| Light type                           | modulated infrared light , 850 nm   |
| Protection field height              | see Table 1, max. 1200 mm   |
| Operating mode                       | Startup/restart disable, deactivateable   |
| Optical resolution                   | 14 mm   |
| Opening angle                        | 5 °   |
| Ambient light limit                  | Not sensitive to ambient light in accordance with IEC 61496-2   |
| UL File Number                       | E215245   |
| Functional safety related parameters |   |
| Safety Integrity Level (SIL)         | SIL 1   |
| Performance level (PL)               | PL c  |
| Category                             | Cat. 2  |
| Mission Time (T <sub>M</sub> )       | 20 a  |
| PFH <sub>d</sub>                     | Depending on the protection field height; see Manual  |
| Type                                 | 2   |
| Indicators/operating means           |   |
| Operation indicator                  | green: Power on   |
| Function indicator                   | Green: OSSD ON , Red: OSSD OFF  |
| Status indicator                     | Transmitter unit: LED yellow: Mode, test or error<br>Receiver: LED yellow: Start readiness, function reserve or error |
| Electrical specifications            |   |
| Operating voltage                    | U <sub>B</sub> 24 V DC (-20%, +30%) ; Power supply with safe isolation: 24 V DC                                       |

Release date: 2023-02-13 Date of issue: 2023-02-13 Filename: 270808\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

## Technical Data

|                                   |       |   |
|-----------------------------------|-------|---|
| No-load supply current            | $I_0$ | Transmitter unit: ≤ 150 mA<br>Receiver: ≤ 150 mA (outputs open) |
| Protection class                  |       | III, IEC 61140  |
| Power consumption                 | $P_0$ | Transmitter unit: 5 W<br>Receiver: 15 W                         |
| <b>Input 1</b>                    |       |   |
| Input type                        |       | Transmitter unit test   |
| Input format                      |       | Break contact   |
| Switching voltage                 |       | 24 V DC   |
| Input current                     |       | 5 mA  |
| <b>Input 2</b>                    |       |   |
| Input type                        |       | Transmitter unit, mode A/B                                      |
| Function                          |       | Beam Code A: open or 0 V<br>Beam Code B: 24 V DC, 5 mA          |
| <b>Input 3</b>                    |       |   |
| Input type                        |       | Receiver unit relay monitor                                     |
| Input format                      |       | Break contact   |
| Switching voltage                 |       | 24 V DC   |
| Input current                     |       | 5 mA  |
| <b>Input 4</b>                    |       |   |
| Input type                        |       | Receiver unit, start release                                    |
| Input format                      |       | Break contact   |
| Input current                     |       | 5 mA  |
| <b>Input 5</b>                    |       |   |
| Input type                        |       | Receiver unit, mode A/B (see transmitter unit, mode A/B)        |
| <b>Output</b>                     |       |   |
| Response time                     |       | see Table 1, max. 54 ms   |
| <b>Output 1</b>                   |       |   |
| Output type                       |       | Receiver unit OSSD  |
| Signal output                     |       | PNP semiconductor, monitored for short and cross circuits       |
| Switching voltage                 |       | ON: $U_B - 2$ V; OFF: < 1 V                                     |
| Switching current                 |       | ON: max. 0.1 A; OFF: < 5 $\mu$ A                                |
| <b>Output 2</b>                   |       |   |
| Output type                       |       | Receiver signal output start readiness                          |
| Signal output                     |       | PNP-semiconductor, short-circuit protected, 0.1A                |
| <b>Conformity</b>                 |       |   |
| Functional safety                 |       | ISO 13849-1 ; EN 61508 part1-4                                  |
| Product standard                  |       | EN 61496-1 ; IEC 61496-2  |
| Photobiological safety            |       | Risk group 0 according to IEC 62471                             |
| <b>Approvals and certificates</b> |       |   |
| CE conformity                     |       | CE  |
| UKCA conformity                   |       | UKCA  |
| UL approval                       |       | cULus Listed  |
| TÜV approval                      |       | TÜV SÜD   |
| <b>Ambient conditions</b>         |       |   |
| Ambient temperature               |       | -35 ... 60 °C (-31 ... 140 °F)                                  |
| Storage temperature               |       | -35 ... 70 °C (-31 ... 158 °F)                                  |
| Relative humidity                 |       | max. 95 %, not condensing                                       |
| Shock resistance                  |       | 10 g, 16 ms ; stationary applications only                      |
| Vibration resistance              |       | 0.35 mm, 10 ... 55 Hz ; stationary applications only            |
| <b>Mechanical specifications</b>  |       |   |
| Housing length L                  |       | see table 2   |
| Degree of protection              |       | IP67, For indoor use only                                       |

Release date: 2023-02-13 Date of issue: 2023-02-13 Filename: 270808\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.comUSA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.comGermany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.comSingapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com


**PEPPERL+FUCHS**

**Technical Data**

|                            |  |
|----------------------------|--|
| Connection                 | Transmitter unit: 4-pin, M12 x 1 connector<br>Receiver: 8-pin, M12 x 1 connector<br>Cable cross section min. 0.25 mm <sup>2</sup><br>Max. cable length 50 m  |
| Material                   |  |
| Housing                    | extruded aluminum section , Silver anodized  |
| Optical face               | Plastic pane , Transparent polycarbonate   |
| Mass                       | see table 2  |
| <b>General information</b> |  |
| Supplementary information  | EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see <a href="http://www.pepperl-fuchs.com">www.pepperl-fuchs.com</a> . |


**Connection**

Transmitter unit:



| Pin | Transmitter unit |
|-----|------------------|
| 1   | 24 V DC          |
| 2   | Mode A/B         |
| 3   | 0 V DC           |
| 4   | Test             |


Receiver unit:




| Pin | Receiver unit          |
|-----|------------------------|
| 1   | Restart Interlock (RI) |
| 2   | 24 V DC                |
| 3   | Relay Monitor (RM)     |
| 4   | Status / Select RI-RM  |
| 5   | OSSD1                  |
| 6   | OSSD2                  |
| 7   | 0 V DC                 |
| 8   | Mode A/B               |

**Assembly**

Transmitter unit




Receiver unit



|   |                  |        |
|---|------------------|--------|
| 1 | Power            | green  |
| 2 | Mode A/B, Status | yellow |
| 3 | OSSD OFF         | red    |
| 4 | OSSD ON          | green  |
| 5 | Restart/Status   | yellow |
| 6 | Mode A/B         | yellow |

Release date: 2023-02-13 Date of issue: 2023-02-13 Filename: 270808\_eng.pdf

## Application



## Technical Features

Table 1: Response Time

| Protection field height [mm] | Response time [ms] |
|------------------------------|--------------------|
| 100                          | 11                 |
| 200                          | 15                 |
| 300                          | 19                 |
| 400                          | 23                 |
| 500                          | 26                 |
| 600                          | 30                 |
| 700                          | 34                 |
| 800                          | 38                 |
| 900                          | 42                 |
| 1000                         | 46                 |
| 1100                         | 50                 |
| 1200                         | 54                 |

Table 2: Total Length and Weight

| Protection field height [mm] | Total length of transmitter/receiver unit [mm] | Weight of transmitter/receiver unit [g] |
|------------------------------|--|---|
| 100                          | 219  | 140                                     |
| 200                          | 319  | 200                                     |
| 300                          | 419  | 250                                     |
| 400                          | 519  | 310                                     |
| 500                          | 619  | 370                                     |
| 600                          | 719  | 430                                     |
| 700                          | 819  | 480                                     |
| 800                          | 919  | 540                                     |
| 900                          | 1019   | 600                                     |
| 1000                         | 1119   | 650                                     |
| 1100                         | 1219   | 710                                     |
| 1200                         | 1319   | 760                                     |

## Type Code

|          |          |          |     |     |     |   |     |     |     |     |   |     |   |     |     |
|----------|----------|----------|-----|-----|-----|---|-----|-----|-----|-----|---|-----|---|-----|-----|
| <b>S</b> | <b>L</b> | <b>C</b> | (1) | (2) | (2) | - | (3) | (3) | (3) | (3) | - | (4) | / | (5) | (5) |
|----------|----------|----------|-----|-----|-----|---|-----|-----|-----|-----|---|-----|---|-----|-----|

| SLC | Device               |
|-----|----------------------|
| SLC | Safety light curtain |

| (1) | Safety light curtain type |
|-----|---------------------------|
| S   | Self-monitoring, type 4   |
| T   | Testing, type 2           |

| (2) | Resolution |
|-----|------------|
| 14  | 14 mm      |
| 30  | 30 mm      |
| 60  | 60 mm      |

Release date: 2023-02-13 Date of issue: 2023-02-13 Filename: 270808\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

## Type Code

| (2) | Resolution |
|-----|------------|
| 90  | 90 mm      |

| (3)  | Protection field height |
|------|-------------------------|
| 100  | 100 mm                  |
| 200  | 110 mm                  |
| 300  | 300 mm                  |
| ...  | ...                     |
| 2400 | 2400 mm                 |















  

| (4) | Principle   |
|-----|-------------|
| T   | Transmitter |
| R   | Receiver    |













| (5) | Option                   |
|-----|--------------------------|
| 35  | Extended detection range |

## Accessories

|   |                          |  |
|---|--------------------------|--|
|    | <b>TR 14/30/50/60</b>    | Test rod for safety light curtain SLCT   |
|    | <b>AA SLCT-01</b>        | Profile alignment aid; simplified alignment of the SLCS and SLCT safety light curtains |
|    | <b>OMH-SLCT-100-1200</b> | Mounting base for floor mounting and cover plate                                       |
|  | <b>OMH-SLCT-100-1500</b> | Mounting base for floor mounting and cover plate                                       |
|  | <b>OMH-SLCT-100-2100</b> | Mounting base for floor mounting and cover plate                                       |
|  | <b>OMH-SLCT-100-2500</b> | Mounting base for floor mounting and cover plate                                       |
|  | <b>OMH-SLCT-110-1200</b> | Mounting base for floor mounting with rear panel and cover plate                       |
|  | <b>OMH-SLCT-110-1500</b> | Mounting base for floor mounting with rear panel and cover plate                       |
|  | <b>OMH-SLCT-110-2100</b> | Mounting base for floor mounting with rear panel and cover plate                       |
|  | <b>OMH-SLCT-120-1200</b> | Side protection for mounting base  |
|  | <b>OMH-SLCT-120-1500</b> | Side protection for mounting base  |
|  | <b>OMH-SLCT-120-2100</b> | Side protection for mounting base  |
|  | <b>OMH-SLCT-120-2500</b> | Side protection for mounting base  |
|  | <b>OMH-SLCT-200</b>      | Floor mount  |

Release date: 2023-02-13 Date of issue: 2023-02-13 Filename: 270808\_eng.pdf

**Accessories**

|   |                        |   |
|---|------------------------|---|
|    | <b>SLCT-M-01-1200</b>  | Inclined mirror for stable 90° deflection with cover plate    |
|    | <b>SLCT-M-01-1500</b>  | Inclined mirror for stable 90° deflection with cover plate    |
|    | <b>SLCT-M-01-2100</b>  | Inclined mirror for stable 90° deflection with cover plate    |
|    | <b>OMH-SLCT-10</b>     | Clamp mounting suitable for 6 mm ... 11.5 mm groove           |
|    | <b>OMH-SLCT-11</b>     | Reverse clamp mounting suitable for 8.5 mm ... 10.5 mm groove |
|    | <b>OMH-SLCT-12-500</b> | Mounting bracket, muting arm with round rod d=12 mm           |
|    | <b>OMH-SLCT-01</b>     | Quick clamp and adjustment system                             |
|    | <b>OMH-SLCT-02</b>     | Attachment aid for OMH-SLCT-01                                |
|   | <b>OMH-SLCT-03</b>     | Mounting bracket including adjustment                         |
|  | <b>OMH-SLCT-04</b>     | Mounting bracket including adjustment (with loose bearing)    |
|  | <b>OMH-SLCT-05</b>     | Mounting bracket including adjustment                         |
|  | <b>OMH-SLCT-06</b>     | Swivel Bracket  |

Release date: 2023-02-13 Date of issue: 2023-02-13 Filename: 270808\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com