



Input coupling link Phased-out product !!! For further information, please contact our sales department Relay coupler in terminal shape 1 NO, 110 V AC/DC

General technical data	
reference code according to IEC 81346-2	K
Substance Prohibittance (Date)	07/01/2006
Weight	0.031 kg
Control circuit/ Control	
control supply voltage at AC	
• at 50 Hz rated value	110 ... 110 V
• at 60 Hz rated value	110 ... 110 V
control supply voltage at DC rated value	110 ... 110 V
supply voltage frequency for auxiliary and control circuit rated value	50 ... 60 Hz
design of the switching function	NO contact
Auxiliary circuit	
type of switching contact	single contact
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	1
number of CO contacts for auxiliary contacts	0
operational current of auxiliary contacts at AC-15	
• at 110 V	3 A
• at 230 V	3 A
operational current of auxiliary contacts at DC-13 at 230 V	0.1 A
Main circuit	
type of voltage	AC/DC
Connections/ Terminals	
type of electrical connection	screw terminal
fastening method	snap-on mounting
height	60 mm
width	11.5 mm
depth	62 mm
ambient temperature during operation	-25 ... +60 °C
Approvals Certificates	
General Product Approval	Test Certificates



[Type Test Certificates/Test Report](#)

[Miscellaneous](#)

other	Environment
-------	-------------

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX7002-2AE00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7002-2AE00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7002-2AE00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7002-2AE00&lang=en

Characteristic: Derating

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7002-2AE00/manual>

last modified:

4/8/2024 