



Output coupling link Phased-out product !!! For further information, please contact our sales department 1 CO,screw terminal 24 V AC/DC enclosure width 6.2 mm

General technical data	
protection class IP	IP20
reference code according to IEC 81346-2	K
Substance Prohibitance (Date)	07/01/2006
Control circuit/ Control	
control supply voltage at AC	
• at 50 Hz rated value	19.2 ... 30 V
• at 60 Hz rated value	19.2 ... 30 V
control supply voltage at DC rated value	30 ... 19.2 V
supply voltage frequency for auxiliary and control circuit rated value	50 ... 60 Hz
design of the switching function	changeover switch
Mechanical data	
design of the relay operating mechanism	poled
Auxiliary circuit	
type of switching contact	single contact
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	1
operational current of auxiliary contacts at AC-15	
• at 230 V	3 A
operational current of auxiliary contacts at DC-13 at 230 V	0.1 A
Main circuit	
type of voltage	AC/DC
Connections/ Terminals	
type of electrical connection	screw terminal
fastening method	snap-on mounting
height	78 mm
width	6.2 mm
depth	87 mm
ambient temperature during operation	-25 ... +60 °C
Approvals Certificates	
General Product Approval	Test Certificates



EG-Konf.



CCC



UL



[Miscellaneous](#)

[Type Test Certificates/Test Report](#)

other

Environment

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX7004-1LB00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7004-1LB00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7004-1LB00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7004-1LB00&lang=en

Characteristic: Derating

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7004-1LB00/manual>

last modified:

4/8/2024 