


Female body



Embout femelle

Body size	Thread	d1	LF	Brass	Steel	AISI 303 stainless	AISI 316 stainless
Taille	Filetage			Laiton	Acier	Inox 303	Inox 316

Female thread BSPP Filetage femelle BSPP

1/8"	1/8	23.9	11/16"	48.3	BH1-60-BSPP	H1-62-BSPP	SH1-62-BSPP	SSH1-62Y-BSPP*
1/4"	1/4	28.0	19 mm	56.9	BH2-60-BSPP	H2-62-BSPP	SH2-62-BSPP	SSH2-62Y-BSPP*
3/8"	3/8	35.4	1"	69.9	BH3-60-BSPP	H3-62-BSPP	SH3-62-BSPP	SSH3-62Y-BSPP*
1/2"	1/2	45.0	1 1/8"	75.4	BH4-60-BSPP	H4-62-BSPP	SH4-62-BSPP	SSH4-62Y-BSPP*
3/4"	3/4	54.4	1 5/16"	93.2	BH6-60-BSPP	H6-62-BSPP	SH6-62-BSPP	SSH6-62Y-BSPP*
1"	1	64.0	1 5/8"	106.2	BH8-60-BSPP	H8-62-BSPP	SH8-62-BSPP	SSH8-62Y-BSPP*


Female thread NPTF Filetage femelle NPTF

1/8"	1/8-27	23.9	11/16"	48.3	BH1-60	H1-62	SH1-62	SSH1-62Y*
1/4"	1/4-18	29.0	13/16"	57.4	BH2-60	H2-62	SH2-62	SSH2-62Y*
3/8"	3/8-18	35.4	7/8"	63.2	BH3-60	H3-62	SH3-62	SSH3-62Y*
1/2"	1/2-14	45.0	1 1/8"	72.9	BH4-60	H4-62	SH4-62	SSH4-62Y*
3/4"	3/4-14	54.4	1 5/16"	93.2	BH6-60	H6-62	SH6-62	SSH6-62Y*
1"	1-11 1/2	64.0	1 5/8"	106.2	BH8-60	H8-62	SH8-62	SSH8-62Y*

Female thread UNF Filetage femelle UNF

1/8"	7/16-20	23.9	11/16"	52.3	BH1-60-T4	H1-62-T4	SH1-62-T4	**
1/4"	9/16-18	29.0	13/16"	61.2	BH2-60-T6	H2-62-T6	SH2-62-T6	**
3/8"	3/4-16	35.4	1"	69.9	BH3-60-T8	H3-62-T8	SH3-62-T8	**
1/2"	7/8-14	45.0	1 1/8"	77.5	BH4-60-T10	H4-62-T10	SH4-62-T10	**
3/4"	1 1/16-12	54.4	1 5/16"	93.2	BH6-60-T12	H6-62-T12	SH6-62-T12	**
1"	1 5/16-12	64.0	1 5/8"	106.2	BH8-60-T16	H8-62-T16	SH8-62-T16	**

Male tip



Embout mâle

Body size	Thread	d2	L	LM	Brass	Steel	AISI 303 stainless	AISI 316 stainless
Taille	Filetage				Laiton	Acier	Inox 303	Inox 316

Female thread BSPP Filetage femelle BSPP

1/8"	1/8	16.1	9/16"	10.5	29.5	BH1-61-BSPP	H1-63-BSPP	SH1-63-BSPP	SSH1-63Y-BSPP*
1/4"	1/4	21.9	19 mm	12.7	34.8	BH2-61-BSPP	H2-63-BSPP	SH2-63-BSPP	SSH2-63Y-BSPP*
3/8"	3/8	25.3	7/8"	19.7	44.7	BH3-61-BSPP	H3-63-BSPP	SH3-63-BSPP	SSH3-63Y-BSPP*
1/2"	1/2	33.4	1 1/8"	16.4	44.5	BH4-61-BSPP	H4-63-BSPP	SH4-63-BSPP	SSH4-63Y-BSPP*
3/4"	3/4	40.3	1 3/8"	21.9	57.7	BH6-61-BSPP	H6-63-BSPP	SH6-63-BSPP	SSH6-63Y-BSPP*
1"	1	47.2	1 5/8"	25.0	65.5	BH8-61-BSPP	H8-63-BSPP	SH8-63-BSPP	SSH8-63Y-BSPP*

Female thread NPTF Filetage femelle NPTF

1/8"	1/8-27	16.5	9/16"	10.5	29.5	BH1-61	H1-63	SH1-63	SSH1-63Y*
1/4"	1/4-18	22.1	3/4"	12.7	35.3	BH2-61	H2-63	SH2-63	SSH2-63Y*
3/8"	3/8-18	25.7	7/8"	13.1	38.1	BH3-61	H3-63	SH3-63	SSH3-63Y*
1/2"	1/2-14	33.0	1 1/8"	16.4	44.5	BH4-61	H4-63	SH4-63	SSH4-63Y*
3/4"	3/4-14	40.4	1 3/8"	19.2	54.9	BH6-61	H6-63	SH6-63	SSH6-63Y*
1"	1-11 1/2	47.8	1 5/8"	25.0	65.5	BH8-61	H8-63	SH8-63	SSH8-63Y*

Female thread UNF Filetage femelle UNF

1/8"	7/16-20	20.2	11/16"	14.5	33.5	BH1-61-T4	H1-63-T4	SH1-63-T4	**
1/4"	9/16-18	25.7	7/8"	12.7	39.1	BH2-61-T6	H2-63-T6	SH2-63-T6	**
3/8"	3/4-16	29.4	1"	19.7	44.7	BH3-61-T8	H3-63-T8	SH3-63-T8	**
1/2"	7/8-14	34.8	1 3/16"	16.4	44.5	BH4-61-T10	H4-63-T10	SH4-63-T10	**
3/4"	1 1/16-12	40.4	1 3/8"	22.0	57.7	BH6-61-T12	H6-63-T12	SH6-63-T12	**
1"	1 5/16-12	47.8	1 5/8"	25.0	65.5	BH8-61-T16	H8-63-T16	SH8-63-T16	**

\* Suffix "Y" designates FPM (Viton™) seal. Consult your Parker sales engineer for seal options.

\*\* Consult your Parker sales engineer for UNF configurations.

**Heavy duty nipples** – Parker 60 series heavy duty nipples are recommended for extended life in applications where high cycle rates and pressure surges are encountered. Machined from high tensile steel and specially hardened. To specify a heavy duty nipple, add the prefix **HD** to the steel 60 series part number, thus : **HDH2-63** and contact us.

**Sleeve-lock** – 60 series couplers (as well as all sleeve type couplers) are available with safety locking sleeves. Please add the suffix **SL** to the part number, eg. **H3-62SL** and contact us.

\*Le suffixe "Y" désigne les joints FPM (Viton™). Nous consulter pour les différentes options de joints.

\*\* Nous consulter pour les configurations UNF.

**Embout mâles haute résistance** – Pour des applications sévères (pointes de pression ou cadence élevée) nous recommandons l'utilisation d'embouts mâles haute résistance. Ajouter le préfixe **HD** à la référence des embouts mâles en acier. Exemple : **HDH2-63** et nous consulter.

**Douille de sécurité** – Les coupleurs série 60 peuvent être équipés d'un dispositif assurant le verrouillage de la douille, afin d'éviter toute manœuvre de désaccouplement accidentel. Ajouter le suffixe **SL** à la référence. Exemple : **H3-62SL** et nous consulter.