



Data sheet

Quick connect coupling

Series 52

Coupling: 52KB

Plug: 52SF

DN: 6 = 30 mm²

Working pressure (static): 0 up to 50 bar

Working temperature: -20°C up to +100°C (depending on the seal material and medium)

Single shut off <input checked="" type="checkbox"/>	Single hand operation <input checked="" type="checkbox"/>	ULTRA-FLO-Valve <input type="checkbox"/>
Double shut off <input type="checkbox"/>	Two hand operation <input type="checkbox"/>	Pipe-valve <input type="checkbox"/>
Straight through <input type="checkbox"/>	Ball locking system <input checked="" type="checkbox"/>	U-Cup-Seal <input type="checkbox"/>
Self venting <input type="checkbox"/>	Pin locking system <input type="checkbox"/>	O-Ring-Seal <input checked="" type="checkbox"/>
Safety lock <input type="checkbox"/>	Coupling anti-splash <input type="checkbox"/>	
Dry Break <input type="checkbox"/>	Plug anti-splash <input type="checkbox"/>	

Materials:

Standard

Version

Back body	Brass, nickel plated
Valve body	Steel, nickel plated
Sleeve	Steel, hardened, nickel plated
Valve	Brass, nickel plated
Spring	AISI 301
Locking Balls / Pins	AISI 420
Seals	Buna N
Plug	Steel, hardened, nickel plated

Description:

The 52KB series is a one hand quick connect coupling made of steel with a good flow rate. The 52KB coupling can be used with a shut-off plug as well as with a straight through plug. Mainly the 52KB series is used for air tools, measuring and control equipment, breathing air, machinery and plant engineering.

Interchangeability:

WALTHER LP-006

Versions / special equipment (in part not for all versions, others upon request):

seal material Buna N, Viton, Kalrez, Ethylen-Propylen;
 surface nickel plated, chrome plated, durnicoat;
 oil and grease free, silicon free;

Test values at 20°C (depending on the version):

Flow-rate air:	1180 l/min at 6 bar inlet pressure and 0,5 bar pressure drop		
Flow-rate water:	14 l/min at 0,5 bar pressure drop		
Vacuum coupling:	min. 87 %	Weight coupling:	app. 150 g
Vacuum plug:	min. - %	Weight plug:	app. 30 g
Vacuum connected:	min. 87 %	Leakage rate / dead volume:	app. - ml
Connecting force:	w/o pressure app. 60 N	at 6 bar inlet pressure	app. 120 N
Disconnecting force:	w/o pressure app. 20 N	at 6 bar inlet pressure	app. 26 N
Safety factor:	at least 4-times	Burst-pressure:	at least 200 bar
Fatigue:	5000 cycles connecting/disconnecting tightness and function O.K.		

Revision	Date	Name		Date	Name	Document-no.: DB-52KB-SF-engl
			Made.	13.04.04	schwab	
			Check	13.04.04	schwab	
			Stand.			