

PSEN cs5.1 M12/8 1switch

542059



RFID safety switch, 2 safe SC outputs, 8-pin M12 male connector, IP67, 4 actuation directions, typ. operating distance (square) 11 mm, $S_{ao} = 8$ mm, $S_{ar} = 20$ mm, PU = 1 piece coded switch.

Technical details

General data	
Approval:	CE, UKCA, cULus Listed, FCC, IC, TÜV, ECOLAB, EAC (Eurasian)
Sensor principle:	Transponder
Coding level to ISO 14119:	gering
Classification to EN 60947-5-3:	PDDB
Transponder coding:	codiert
Suitable for series connection:	ja
unit type:	Sensor
Technical data	
Electrical data	
Supply voltage (V):	24
Type of supply voltage U1:	DC
Power consumption DC:	1
Inputs	
Number of inputs:	2
DC voltage at input:	24 V DC
Semiconductor outputs	
Number of OSSD outputs:	2
Number of sig. outputs:	1
Potential isolation S/C O:	nein

S/C output short circuit proof:	ja
Utilisation cat. to EN 60947-1:	DC-12
Environmental data	
Ambient temperature standard:	EN 60068-2-14
Ambient temperature:	-25
Max. ambient temp. at Hmax:	+60 °C
Max. ambient temp. at 2000 m:	+70 °C
Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-30
Humidity rating:	93 % r. F. bei 40 °C
Perm. operating height ASL:	4000 m
EMC to standard ...:	EN 60947-5-3
Vibration to standard ...:	EN 60947-5-2
Acc. shock to standard1:	30g
Overvoltage category:	III
Pollution degree clear.&creep.:	3
Protection type, housing:	IP66, IP67
Switching distances	
Change op. distance temp.act.1:	+0,02mm/°C
Change op. distance temp.act.2:	+0,02mm/°C
Change op. distance temp.act.3:	+0,02mm/°C
Mechanical data	
Sensor can be flush-mounted:	Ja, Montagehinweis beachten
Connection type:	M12, 8-pin male
Product material:	PBT, PA+GF, Polycarbonat
Height dimension:	26.4
Width dimension:	101.6
Depth dimension:	19
Net weight:	68

Gross weight:	78
Transponder	
Operating frequency:	122 kHz - 128 kHz
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	0
RoHS exceptions:	0
RoHS except.s acc. to direct.:	7C I
REACH compliance:	1
REACH included substances:	Bleioxid
%-part of the pollutant:	> 0,1%
CAS No.:	1317-36-8
WEEE klassifikation (08/2018):	5
SCIP entry available:	yes
Commercial data	
Harmonized System Code:	85365019
UNSPSC 25:	39122205
EAN-Code:	4046548077421
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27274601
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC002592
Volume:	0 dm3

Obligatory accessories

542088

PSEN cs5.1 low profile screw 1 actuator





542087

PSEN cs5.1 low profile glue 1 actuator



542083

PSEN cs5.1 M12 1 actuator

Optional accessories



540324

PSEN cable angle M12 8-pole 10m



540325

PSEN cable angle M12 8-pole 30m




540326

PSEN cable axial M12 8-pole 30m



535111

PSEN ix2 F4 code



535112

PSEN ix2 F8 code



540342

PSEN cable M12-8sf M12-8sm, 10m



540320

PSEN cable axial M12 8-pole 5m



540343

PSEN cable M12-8sf M12-8sm, 20m



540321

PSEN cable axial M12 8-pole 10m



540344

PSEN cable M12-8sf M12-8sm, 30m



540322

PSEN cable angle M12 8-pole 3m



540323

PSEN cable angle M12 8-pole 5m



540130

SDD ES ETH



773613

PDP67 F 4 code VA



540313

PSEN screw M4x20 10pcs



540314

PSEN screw M4x26 10pcs



540138

SDD ES PROFINET



540315

PSEN Y junction M12 SENSOR



540337

PSEN Y junction M8-M12/M12 PIGTAIL



540338

PSEN Y junction M12-M12/M12 PIGTAIL



540316

PSEN Y junction M12 cable channel



540331

PSEN T junction (auxiliary contact) M12



540333

PSEN cable M12-8sf, 20m



532111

PSEN mag/cs bracket straight



532110

PSEN Winkel / bracket



540319

PSEN cable axial M12 8-pole 3m



532109

PSEN cs bracket stop sliding door



532108

PSEN cs bracket stop swinging door



540340

PSEN cable M12-8sf M12-8sm, 2m



540341

PSEN cable M12-8sf M12-8sm, 5m



773603

PDP67 F 4 code