

Solenoid Valves

Technical characteristics table

2-way valves

Reference	Function	Connection	Body material	Orifice (mm)	Qn (l/min)	Pressure range (bar)	Seat seal	Weight of solenoid valve (g)	Drawing
121F67	2/2 NF	Flanged	Brass	1.5	80	0-25	Ruby	280	A
121F4606	2/2 NF	Flanged	Brass	2	140	0-10	FKM	280	A
121F63	2/2 NF	Flanged	Brass	2.5	220	0-10	Ruby	280	A
121F64	2/2 NF	Flanged	Brass	3	320	0-7	Ruby	280	A
E121K0402	2/2 NF	¼"G	Brass	1.5	80	0-20	FKM	320	B
E121K04	2/2 NF	¼"G	Brass	1.5	80	0-25	PCTFE	320	B
121K0605	2/2 NF	¼"G	Brass	2	140	0-10	FKM	320	B
E121K07	2/2 NF	¼"G	Brass	2.5	220	1-10	PCTFE	320	B
E121K63	2/2 NF	¼"G	Brass	2.5	220	0-10	Ruby	280	B
121K0302	2/2 NF	¼"G	Brass	3	320	0-7	FKM	280	B
E121K45	2/2 NF	½"G	Brass	11	2,500	0-0.3	FKM	430	C
121V5163	2/2 NF	¼"G	Stainless steel	5	(kV 10)	0-2	Ruby	410	D
122K8406	2/2 NO	¼"G	Brass	1.5	80	0-20	FKM	320	B
122K8408	2/2 NO	¼"G	Brass	1.5	80	0-40	Ruby	320	B
122K8306	2/2 NO	¼"G	Brass	2.5	200	0-12	FKM	320	B
122K8311	2/2 NO	Pilot	-	2.5	200	0-12	FKM	320	B
122KS4074A	2/2 NO	20 mm dia.	Brass	18	(kV 50)	0-2	FKM	930	-

3-way valves

Reference	Function	Connection	Body material	Orifice (mm) (1) (2)	Qn (l/min)	Pressure range (bar)	Seat seal	Weight of solenoid valve (g)	Drawing
131FS9366*	3/2 NF	Flanged	Brass	1.5 / 1.5	80 / 80	2-10	PUR	280	E
E131F44	3/2 NF	Flanged	Brass	1.5 / 1.5	80 / 80	0-15	FKM	280	E
131F46	3/2 NF	Flanged	Brass	2 / 2.5	140 / 220	0-10	FKM	280	E
131F4650*	3/2 NF	Flanged	Brass	2 / 2.5	140 / 220	0-10	FKM	280	E
E131F43	3/2 NF	Flanged	Brass	2.5 / 2.5	220 / 220	0-7	FKM	280	E
E131F4350*	3/2 NF	Flanged	Brass	2.5 / 2.5	220 / 220	0-7	FKM	280	E
E131K04	3/2 NF	¼"G	Brass	1.5 / 1.5	80 / 80	0-16	FKM	320	F
E131K06	3/2 NF	¼"G	Brass	2 / 2.5	140 / 220	0-10	FKM	320	F
E131K03	3/2 NF	¼"G	Brass	2.5 / 2.5	220 / 220	0-7	FKM	320	F
131M74	3/2 NF	Flanged	Brass	1.5 / 1.5	70 / 70	0-7	FKM	120	G
131M75	3/2 NF	Flanged	Brass	1.2 / 1.5	50 / 70	0-10	FKM	120	G
131T21	3/2 NF	¼"G	Brass	4.5 / 6	500 / 750	0-2	FKM	400	H
132F44	3/2 NO	Flanged	Brass	1.5 / 1.5	80 / 80	0-16	FKM	280	E
132F46	3/2 NO	Flanged	Brass	2 / 2	125 / 125	0-10	FKM	280	E
132F4301	3/2 NO	Flanged	Brass	2.5 / 2.5	160 / 160	0-9	PUR	280	E
132K04	3/2 NO	¼"G	Brass	1.5 / 1.5	80 / 80	0-16	FKM	320	F
133F46	3/2 Universal	Flanged	Brass	2 / 2	140 / 140	0-7	FKM	280	E

* With manual control.