

6ES7138-4CA00-0AA0**SIMATIC DP, POWER MODULE PM-E****Technical data**

SIMATIC DP, POWER MODULE PM-E FOR ET 200S; 24V DC WITH DIAGNOSIS

Supply voltage	
external protection for power supply lines (recommendation)	Yes, tripping characteristic C
Load voltage L+	
• Rated value (DC)	24 V
• Short-circuit protection	No; external (e.g. automatic circuit breaker)
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	4 mA
Current carrying capacity	
up to 60 °C, max.	10 A
Power loss	
Power loss, typ.	0.1 W
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Diagnoses	
• Diagnostic information readable	Yes
• missing load voltage	Yes
Diagnostics indication LED	
• Rated load voltage PWR (green)	Yes
• Group error SF (red)	Yes
Parameter	
Remark	3 byte
missing load voltage	Disable / enable
Potential separation	
primary/secondary	Yes; between rated load voltage and backplane bus, between power modules
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	35 g
last modified:	12/10/2020

Last changes: 12/10/2020