



SIMATIC S7-300, FUNCTION MODULE FM 353, FOR POSITIONING WITH STEPPER MOTOR, MODULE EXCHANGE W/O PG, PREREQUISITE STEP7 V3.1 INCL. CONFIG. PACKAGE ON CD

Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, max.	300 mA
Power loss	
Power loss, typ.	7 W
Digital inputs	
Number of digital inputs	4; + 1 input for message signal
Functions	Reference cams, flying actual value setting, flying measurement, start/stop positioning, external block change
Input voltage	
- Rated value (DC) - for signal "0" - for signal "1"	24 V -3 to +5V +11 to +30V
Input current	
- for signal "0", max. (permissible quiescent current) - for signal "1", typ.	2 mA 6 mA; 6 to 15 mA
Digital outputs	
Number of digital outputs	4
Functions	Position reached: stop, axis travels forward, axis travels back, change M-function M97, change M-function M98, start enable, direct output via data record
Short-circuit protection	Yes
Output voltage	
- Rated value (DC) - for signal "1", min.	24 V UP -3 V
Output current	
- for signal "1" permissible range for 0 to 55 °C, max. - for signal "0" residual current, max.	0.6 A; with UPmax 2 mA
Drive interface	
Signal Input	
Function	"Power section ready"
Stepper drive	
- Differential output voltage, min. - Differential output voltage for signal "0", max. - Differential output voltage for signal "1", min. - Cable length, shielded, max.	2 V; RL = 100 Ohm 1 V; Io = 20 mA 3.7 V; Io = -20 mA 35 m
Potential separation	
Potential separation digital inputs	

• Potential separation digital inputs	No
Potential separation digital outputs	
• Potential separation digital outputs	No
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
connection method	
required front connector	1x 20-pin
Dimensions	
Width	80 mm
Height	125 mm
Depth	118 mm
Weights	
Weight, approx.	500 g
Classifications	

	Version	Classification
eClass	14	27-24-22-05
eClass	12	27-24-22-05
eClass	9.1	27-24-22-05
eClass	9	27-24-22-05
eClass	8	27-24-22-05
eClass	7.1	27-24-22-05
eClass	6	27-24-22-05
ETIM	10	EC001422
ETIM	9	EC001422
ETIM	8	EC001422
ETIM	7	EC001422
IDEA	4	3567
UNSPSC	15	32-15-17-05

Approvals / Certificates		
General Product Approval	For use in hazardous locations	Maritime application

[Miscellaneous](#)

[KC](#)



[NK / Nippon Kaiji Kyokai](#)

Maritime application



last modified: 5/23/2024