

product type designation



CP 443-1

***** spare part ***** communications processor CP 443-1 for connection of SIMATIC S7-400 to industrial Ethernet via ISO/TCP/IP and UDP, S7 communication, fetch/write, diagnostics extensions, send/receive, with and without RFC1006, multicast, NTP, initialization via LAN, access protection via IP access list 10/100 Mbit.

transfer rate	
transfer rate	
<ul style="list-style-type: none"> at the 1st interface 	10 ... 100 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	1
number of electrical connections	
<ul style="list-style-type: none"> at the 1st interface / according to Industrial Ethernet 	1
type of electrical connection	
<ul style="list-style-type: none"> of Industrial Ethernet interface 	15 pin Sub-D-socket (10Mbit/s AUI, 10/100 Mbit/s ITP)
<ul style="list-style-type: none"> at the 1st interface / according to Industrial Ethernet 	RJ45 port / AUI
design of the removable storage	
<ul style="list-style-type: none"> C-PLUG 	No
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
supply voltage	5 V
relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> at 5 V 	5 %
consumed current	
<ul style="list-style-type: none"> from backplane bus / at DC / at 5 V / typical 	1.4 A
power loss [W]	8.6 W
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation 	0 ... 60 °C
<ul style="list-style-type: none"> during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> during transport 	-40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-400 single width
width	25 mm
height	290 mm
depth	210 mm
net weight	0.7 kg
product features, product functions, product components / general	
number of units	
<ul style="list-style-type: none"> per CPU / maximum 	14

performance data / open communication	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	64
data volume	
<ul style="list-style-type: none"> as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum 	2 Kibyte
performance data / S7 communication	
number of possible connections / for S7 communication	
<ul style="list-style-type: none"> maximum 	48
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	64
product functions / management, configuration, engineering	
product function / MIB support	No
protocol / is supported	
<ul style="list-style-type: none"> SNMP v1 	No
<ul style="list-style-type: none"> LLDP 	No
configuration software	
<ul style="list-style-type: none"> required 	STEP 7 V5.1 SP2 or higher
product functions / diagnostics	
product function / web-based diagnostics	No
product functions / switch	
product feature / switch	No
product functions / redundancy	
product function	
<ul style="list-style-type: none"> ring redundancy 	No
product functions / security	
product function	
<ul style="list-style-type: none"> password protection for Web applications 	No
<ul style="list-style-type: none"> ACL - IP-based 	No
<ul style="list-style-type: none"> ACL - IP-based for PLC/routing 	No
<ul style="list-style-type: none"> switch-off of non-required services 	No
<ul style="list-style-type: none"> blocking of communication via physical ports 	No
<ul style="list-style-type: none"> log file for unauthorized access 	No
product functions / time	
product function / SICLOCK support	Yes
product function / pass on time synchronization	No
protocol / is supported	
<ul style="list-style-type: none"> NTP 	Yes
further information / internet links	
internet link	
<ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool 	http://www.siemens.com/tia-selection-tool
<ul style="list-style-type: none"> to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> to website: CAX-Download-Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> to website: Industry Online Support 	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is

necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval	EMV	For use in hazardous locations
---------------------------------	------------	---------------------------------------

[Declaration of Conformity](#)



[KC](#)

[KC](#)



For use in hazardous locations	Marine / Shipping
---------------------------------------	--------------------------

[EM](#)



[Type Examination Certificate](#)



Marine / Shipping	Environment
--------------------------	--------------------

[CCS \(China Classification Society\)](#)

[Confirmation](#)

last modified:

5/22/2024