## SIEMENS

## Data sheet

## 6GT2821-1AC10

product type designation

suitability for operation

## RF210R reader

SIMATIC RF200 reader RF210R; RS422 interface (3964R); IP67, -25 to +70 °C; M18x 71mm; with integrated antenna.

ISO 15693 Transponder (MDS Dxxx), for connecting to communication



suitability for operation	modules		
radio frequencies			
operating frequency / rated value	13.56 MHz		
range / maximum	20 mm; Range is dependent on transponder type: observe http://support.automation.siemens.com/WW/view/en/67384964		
protocol / with radio transmission	ISO 15693, ISO 18000-3		
transfer rate / with radio transmission / maximum	26.5 kbit/s		
product feature / multitag-capable	No		
electrical data			
transfer rate / at the point-to-point connection / serial / maximum	115.2 kbit/s		
transmission time / for user data			
<ul> <li>for write access / per byte / typical</li> </ul>	0.6 ms		
<ul> <li>for read access / per byte / typical</li> </ul>	0.6 ms		
interfaces			
standard for interfaces / for communication	RS422		
type of electrical connection	M12, 8-pin		
mechanical data			
material	Brass, nickel-plated / PBT		
color	silver/pastel turquoise		
tightening torque / of the screw for securing the equipment / maximum	20 N·m		
mounting distance / relating to metal surfaces / recommended / minimum	0 mm		
supply voltage, current consumption, power loss			
supply voltage / at DC			
rated value	24 V		
•	20.4 28.8 V		
consumed current / at DC			
• at 24 V / typical	0.05 A		
ambient conditions			
ambient temperature			
during operation	-20 +70 °C		
during storage	-25 +80 °C		
during transport	-25 +80 °C		
protection class IP	IP67		
shock resistance	EN 60721-3-7 Class 7 M2		
shock acceleration	500 m/s²		
vibrational acceleration	200 m/s²		
design, dimensions and weights			

height	83 mm			
diameter	18 mm			
net weight	0.065 kg			
fastening method	2 nuts M18 x 1 (included in sco	ope of supply)		
wire length		· · · · · · · · · · · · · · · · · · ·		
<ul> <li>for RS 422 interface / maximum</li> </ul>	1000 m			
product features, product functions, product components / general				
display version	3-color LED			
product feature / silicon-free	Yes			
standards, specifications, approvals				
certificate of suitability	Radio according to R&TTE gui	delines EN300 330 and E	EN 301489, FCC, cULus	
certificate of suitability				
• IECEx	No			
MTBF	505 a			
reference code				
<ul> <li>according to IEC 81346-2:2019</li> </ul>	ВҮВ			
further information / internet links				
internet link				
<ul> <li>to website: Selection guide for cables and connectors</li> </ul>	https://support.industry.siemens.com/cs/ww/en/view/109766358			
<ul> <li>to web page: selection aid TIA Selection Tool</li> </ul>	https://www.siemens.com/tstcloud			
• to web page: RFID country approval	https://www.siemens.com/rfid-approvals			
• to web page: identification and localization systems	https://www.siemens.com/ident			
• to web page: SiePortal	https://sieportal.siemens.com/			
<ul> <li>to website: Image database</li> </ul>	https://www.automation.siemens.com/bilddb			
<ul> <li>to website: CAx-Download-Manager</li> </ul>	https://www.siemens.com/cax			
<ul> <li>to website: Industry Online Support</li> </ul>	https://support.industry.siemens.com			
security information				
Approvals / Certificates	In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)			
General Product Approval		EMV	Radio Equipment Type Approval Certi-	
			ficate	
		KC	<u>Miscellaneous</u>	
Environment				
Confirmation				
Confirmation				
last modified:	8/18/2024 🖸			

12/12/2024