



Figure similar

MLFB-Ordering data                      6SE6440-2UD21-1AA1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Rated data                       |                     | General tech. specifications |               |
|----------------------------------|---------------------|------------------------------|---------------|
| Input                            |                     | Power factor λ               | 0.95          |
| Number of phases                 | 3 AC                | Efficiency η                 | 0.96          |
| Line voltage                     | 380 ... 480 V ±10 % | Ambient conditions           |               |
| Line frequency                   | 47 ... 63 Hz        | Cooling                      | Fan           |
| Rated current (HO)               |                     | Ambient temperature          |               |
| 4.90 A                           |                     | Operation (HO)               | -10 ... 50 °C |
| Output                           |                     | Transport                    | -40 ... 70 °C |
| Number of phases                 | 3 AC                | Storage                      | -40 ... 70 °C |
| Rated voltage                    | 480 V               |                              |               |
| Rated power (HO)                 | 1.10 kW / 1.50 hp   |                              |               |
| Rated current (HO)               | 3.10 A              |                              |               |
| Pulse frequency                  | 4000 Hz             |                              |               |
| Output frequency for V/f control | 0 ... 650 Hz        |                              |               |

As a result of legal stipulations, a limit to 550 Hz is in production

### Overload capability

#### High Overload (HO)

150 % output current for 60 s, followed by 100 % output current for 240 s in a 300 s cycle time

MLFB-Ordering data                      6SE6440-2UD21-1AA1



Figure similar

| Mechanical data      |                     | Connections             |          |
|----------------------|---------------------|-------------------------|----------|
| Degree of protection | IP20 / UL open type | Motor end               |          |
| Frame size           | FSA                 | Conductor cross-section | 2.50 mm² |
| Net weight           | 1.30 kg             |                         |          |
| Width                | 73.0 mm             |                         |          |
| Height               | 173.0 mm            |                         |          |
| Depth                | 149.0 mm            |                         |          |

| Inputs / outputs        |   |
|-------------------------|---|
| Standard digital inputs |   |
| Number                  | 6 |
| Relay output            |   |
| Number                  | 3 |
| Analog inputs           |   |
| Number                  | 2 |
| Analog outputs          |   |
| Number                  | 2 |
| PTC/ KTY interface      |   |
| Number                  | 1 |