

MORE INFO



- Cabinets are standard factory assembled (empty or equipped)
Complete with handle and wall mounting brackets of AISI 304 stainless steel (without cylinder lock)
- Material: self-extinguishing, hot moulded, halogen-free, fiberglass reinforced polyester (environment friendly)
- Coupling possibilities in height, width and depth
- Door with 5-point latching mechanism
- Execution as pedestal possible
- Rated insulation voltage $U_i = 1000V$
- Corrosion and maintenance free
- Easy recyclable: no moulded-in metal parts

Ambient conditions

- Subterranean installation
- Suitable for aggressive and marine or corrosive environments
- Indoor and outdoor stationary use, excluding:
artic conditions below $-50^{\circ}C$,
excessive heat above $+150^{\circ}C$ (peak) and excessive height above 2000 m

SPECIFICATIONS

Enclosure type	Cabinet
Family Name	Polysafe
Total Insulation	Yes
Raw materials	Polyester glass-fibre reinforced hot-moulded
Ambient conditions	Indoor;Outdoor
Installation	Floor standing;Pole Fixing;Wall mounting
IP	IP65
Product/Accessory	Product

Product/Accessory functionality	Cabinet
Door/Cover	Door
Door/Cover- plain/glazed	Plain
Standards	EN 60529;EN 62208;EN 62262;IEC 60529;IEC 62208;IEC 62262
Approvals	CSA;UL
Type	PS 320
IK	IK10
Kind of closing system	With handle without cylinder lock
Screws/Hinges/Bolts	Hinges
Colour	RAL 7035
Volume	0.12 m3
Standard packing	1

DIMENSIONS

750 mm

500 mm

320 mm

Weight 20 kg

CLASSIFICATION

ETIM 6.0 EC000058

