



AES1337

- Monitoring of BNS range magnetic safety sensors
- 3 safety contacts, STOP 0
- 1 Signalling output

Data

Ordering data

Note (Delivery capacity)	Phased-out product
Product type description	AES1337
Article number (order number)	101172210
EAN (European Article Number)	4250116201839
eCl@ss number, version 12.0	27-37-18-19
eCl@ss number, version 11.0	27-37-18-19
eCl@ss number, version 9.0	27-37-18-19
ETIM number, version 7.0	EC001449
ETIM number, version 6.0	EC001449
Available until	31.12.2024

Approvals - Standards

Certificates	cULus CCC
--------------	--------------

General data

Standards	BG-GS-ET-14
	EN IEC 62061
	EN ISO 13849-1
	EN IEC 60947-5-1
	EN IEC 60947-5-3
	EN IEC 60947-5-5
	EN IEC 61508
	EN IEC 60204-1
	EN IEC 60947-1
Climatic stress	EN 60068-2-78
Housing material	Glass-fibre reinforced thermoplastic, ventilated
Gross weight	280 g

General data - Features

Electronic Fuse	Yes
Wire breakage detection	Yes
Cross-circuit detection	Yes
Start input	Yes
Feedback circuit	Yes
Automatic reset function	Yes
Reset edge detection	Yes
Earth connection detection	Yes
Integral system diagnostics, status	Yes
Number of auxiliary contacts	1
Number of LEDs	4
Number of normally closed (NC)	1
Number of normally open (NO)	1
Number of safety contacts	3

Safety classification

Standards	EN IEC 60947-5-1
	EN IEC 61508
Stop-Category	0

Safety classification - Relay outputs

Performance Level, up to	e
Category	4
Diagnostic Coverage (DC) Level	$\geq 99\%$
PFH value	$2.00 \times 10^{-8} / \text{h}$
Safety Integrity Level (SIL), suitable for applications in	3
Mission time	20 Year(s)
Common Cause Failure (CCF), minimum	65

Mechanical data

Mechanical life, minimum	10,000,000 Operations
Mounting	Snap onto standard DIN rail to EN 60715

Mechanical data - Connection technique

Terminal designations	IEC/EN 60947-1
Termination	rigid or flexible Screw terminals M20 x 1.5
Cable section, minimum	0.25 mm ²
Cable section, maximum	2.5 mm ²
Tightening torque of Clips	0.6 Nm

Mechanical data - Dimensions

Width	22.5 mm
Height	100 mm
Depth	121 mm

Ambient conditions

Degree of protection of the enclosure	IP40
Degree of protection of the mounting space	IP54
Degree of protection of clips or terminals	IP20
Ambient temperature	-25 ... +45 °C
Storage and transport temperature	-40 ... +85 °C
Resistance to vibrations	10 ... 55 Hz, Amplitude 0.35 mm
Resistance to shock	10 g / 11 ms

Ambient conditions - Insulation values

Overvoltage category	III
Degree of pollution	2

Electrical data

Frequency range	50 Hz 60 Hz
Thermal test current	6 A
Rated AC voltage for controls, 50 Hz, minimum	20.4 VAC
Rated control voltage at AC 50 Hz, maximum	26.4 VAC
Rated AC voltage for controls, 60 Hz, minimum	20.4 VAC
Rated control voltage at AC 60 Hz, maximum	26.4 VAC
Rated AC voltage for controls at DC minimum	20.4 VDC
Rated control voltage at DC, maximum	28.8 VDC
Electrical power consumption	2.1 W
Electrical power consumption	3.5 VA
Contact resistance, maximum	0.1 Ω
Note (Contact resistance)	in new state

Drop-out delay in case of power failure, typically	80 ms
Drop-out delay in case of emergency, typically	20 ms
Pull-in delay at automatic start, maximum, typically	100 ms
Pull-in delay at RESET, typically	20 ms
Material of the contacts, electrical	AgSn0. self-cleaning, positive drive

Electrical data - Safe relay outputs

Voltage, Utilisation category AC-15	230 VAC
Current, Utilisation category AC-15	6 A
Voltage, Utilisation category DC-13	24 VDC
Current, Utilisation category DC-13	6 A
Switching capacity, minimum	10 VDC
Switching capacity, minimum	10 mA
Switching capacity, maximum	250 VAC
Switching capacity, maximum	8 A

Electrical data - Digital inputs

Conduction resistance, maximum	40 Ω
--------------------------------	-------------

Electrical data - Relay outputs (auxiliary contacts)

Switching capacity, maximum	24 VDC
Switching capacity, maximum	2 A

Electrical data - Electromagnetic compatibility (EMC)

EMC rating

EMC-Directive

Status indication

Indicated operating states	Position relay K2
	Position relay K1
	Internal operating voltage U_i

Other data

Note (applications)	Safety sensor Guard system
---------------------	-------------------------------

Note

Note (General)	Inductive loads (e.g. contactors, relays, etc.) are to be suppressed by means of a suitable circuit.
----------------	--

Wiring example

Note (Wiring diagram)	The wiring diagram is shown with guard doors closed and in de-energised condition. Monitoring 1 guard door(s), each with a magnetic safety sensor of the BNS range The feedback circuit monitors the position of the contactors K3 and K4. To secure a guard door up to PL e and Category 4 Automatic start: The automatic start is programmed by connecting the feedback circuit to the terminals X1/X3. If the feedback circuit is not required, establish a bridge. Start button (S) with edge detection
-----------------------	---


Pictures

Product picture (catalogue individual photo)



ID: kaes1f23
| 831.7 kB | .jpg | 265.994 x 625.122 mm - 754 x 1772 px - 72 dpi
| 103.5 kB | .png | 74.083 x 173.919 mm - 210 x 493 px - 72 dpi
| 42.7 kB | .jpg | 52.564 x 123.472 mm - 149 x 350 px - 72 dpi

Wiring example



ID: kaes1I39
| 11.3 kB | .swf |
| 148.0 kB | .jpg | 352.778 x 334.081 mm - 1000 x 947 px - 72 dpi

Symbol (technical standard)

K	n-op/y	t-cycle
20 %	525.600	1,0 min
40 %	210.240	2,5 min
60 %	75.087	7,0 min
80 %	30.918	17,0 min
100 %	12.223	43,0 min

ID: kformm02
| 191.1 kB | .jpg | 352.778 x 246.592 mm - 1000 x 699 px - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on: 29/11/2024, 14:02