

T compression ring fitting 15 (M20x1.5)mm, brass

Item number:

KT 15 MS



Example illustration

Item description

Temperature range:

-60°C up to max. +300°C (with seal: -20°C up to max. +80°C)

Recommended raw materials:

Copper, polyamide (with reinforced sleeve)

Note:

The brass compression ring screw connections cannot be combined with the cutting ring pipe screw connectors ISO 8434-1 (DIN 2353). When using soft copper tube a correction factor of 0.65 must be used (pressure x 0.65). When using polyamide tube the operating pressure of the tube applies.

Materials:

brass

Properties

Pipe diameter (outer) [mm]	15 (M20x1.5)
Operating pressure with hard copper tube [bar]	82
Temperature range [°C]	-60 to +300

Further information:

Weight	170 g / pcs
GTIN	4050571457358
Customs duty number	74122000
RoHS compliant	Yes

More information on this item and the process for ordering it can be found in our online shop
<https://www.landefeld.com> under item number **KT 15 MS**.

Landefeld Druckluft und Hydraulik GmbH · Konrad-Zuse-Straße 1 · 34123 Kassel · Germany

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.

As of: 13.05.2024