

Data sheet

LANDEFELD

glycerine pressure gauge horizontal
(CrNi/Ms), 63 mm, -1 to 3 bar

Item number:
MW -1363 GLY CR



Example illustration

Item description

Materials:
Housing: 1.4301, measuring system: Cu alloy (pressures >400 bar: 1.4404), connection: brass, Window: transparent plastic

Connection thread:
G 1/4" *, rear side central

Class:
1,6

Temperature range:
-20°C to +60°C

Dial:
1. Scale outside (black), display in bar, 2. scale inside (red), display in PSI

Protection class:
IP 65

Note:
WIKA Type 213.53

Optional:
Connection 1/4" NPT-thread **-NPT**, ISO calibration certificate (factory calibration certificate) acc. to DIN EN ISO 17025, VDI and data sheet DAKK5-DKD-MB-3 with 5 measurement points

Properties

Display range [bar]	-1 to 3
Connection thread	G 1/4" *
Scale division [bar]	0,2

Further information:

Weight	230 g / pcs
GTIN	4050571511784
Customs duty number	90262040
Manufacturer	Wika

More information on this item and the process for ordering it can be found in our online shop
<https://www.landefeld.com> under item number **MW -1363 GLY CR**.

Landefeld Druckluft und Hydraulik GmbH · Konrad-Zuse-Straße 1 · 34123 Kassel · Germany

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.

As of: 07.07.2023