

Data sheet

Elbow push in fitting G 1/4"-8mm, Model series C

Item number:

RIB 18 08 13 C



Example illustration

Item description

Model series topline, C and CV**Materials:**

Body: nickel-plated brass, seal: NBR (CV model series: FKM), sleeve: nickel-plated brass (Topline model series: plastic)

Temperature range:

-20°C to max. +70°C (Model series CV: max. +150°C)

Operating pressure:

-0,95 to 15 bar

Model series stainless steel**Materials:**

Body: stainless steel (316), seal: FKM, sleeve: stainless steel (316)

Temperature range:

-15°C up to max. +110°C

Operating pressure:

-0,95 to 18 bar

Information:

Only use silicone free seals and lubricants during assembly!

Properties

Model series	Model series C
G	G 1/4"
D [mm]	8

Temperature range [°C]	-20 to +70
Operating pressure [bar]	-0.95 to 15

Further information:

Weight	50 g / pcs
GTIN	4050571585068
Customs duty number	74122000
RoHS compliant	Yes

More information on this item and the process for ordering it can be found in our online shop
<https://www.landefeld.com> under item number **RIB 18 08 13 C**.

Landefeld Druckluft und Hydraulik GmbH · Konrad-Zuse-Straße 1 · 34123 Kassel · Germany

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.

As of: 27.06.2023