

K Series is a full range of direct operated solenoid valves, from 1/8" to 1/2", offering many sealing materials and different rates.

[Share / Email](#)

---

## Technical Specifications

**Seal Material:**

FKM

**Power Supply Voltage:**

-

**Coil Specifications Met:**

-

**Port Size:**

1/4" G

**Maximum Operating Pressure:**

7 bar AC/DC

**Valve Type:**

3/2 Way

**Specifications Met:**

-

**Function:**

Universal

**ATEX Specifications Met:**

-

**Orifice Size:**

2,0 mm

**Coil Power Consumption:**

-

**Electrical Connection:**

-

**Actuation Type:**

Direct Operated

**Port Type:**

Pipe Mounting

**Body Material:**

CW 617N UNI EN 12165

**Media:**

Air, Neutral Gases, Liquids

**Seat Material:**

Stainless Steel

**Exhaust Orifice Size:**

2,0 mm

**Flow Coefficient 1:**

2,5 L/min

**Flow Coefficient 2:**

0,15 m<sup>3</sup>/hour

**Minimum Operating Pressure:**

0 bar

**Minimum Fluid Temperature:**

-10 °C

**Maximum Fluid Temperature:**

120 °C

**Coil Temperature Range:**

-

**Insulation Class:**

-