


































**"S" Series Individual Subbase Valves Size 1 (Valve & Base without Pneumatic Connectors)**

		Symbol	Type	Cv	Operator	Part number
Moduflex Series			4-way, 2-position	0.32	Single solenoid	<b>P2M1S4ES2C</b>
					Single air pilot	<b>P2M1S4PS</b>
			4-way, 2-position	0.32	Double solenoid	<b>P2M1S4EE2C</b>
					Double air pilot	<b>P2M1S4PP</b>
			3-way, 2-position, dual valve, NC/NC w/ exhaust check	0.22	Double solenoid	<b>P2M1SDEE2C</b>
					Double air pilot	<b>P2M1SDPP</b>
Isys Micro Series			3-way, 2-position, dual valve, NO/NO w/ exhaust check	0.22	Double solenoid	<b>P2M1SC EE2C</b>
					Double air pilot	<b>P2M1SCPP</b>
Isys ISO Series			3-way, 2-position, dual valve, NC/NO w/ exhaust check	0.22	Double solenoid	<b>P2M1SEEE2C</b>
					Single solenoid	<b>P2M1S3ES2C</b>
			3-way, 2-position, NC w/ exhaust check	0.22	Single air pilot	<b>P2M1S3PS</b>
			3-way, 2-position, dual valve, NC/NC	0.22	Double solenoid	<b>P2M1SGEE2C</b>







**"S" Series Size 1 Accessories**

	Description	Tube Size	Option	Part number
	Size 1 push to connect fitting	5/32"	Elbow	<b>CMD04-1</b>
			Straight	<b>FMD04-1</b>
	Size 1 push to connect fitting	1/4"	Elbow	<b>CMD07-1B</b>
			Straight	<b>FMD07-1B</b>
	Size 1 push to connect fitting	6mm	Elbow	<b>CMD06-1</b>
			Straight	<b>FMD06-1</b>
	Muffler for exhaust port			<b>MMDVA1</b>
	Plug			<b>PMDYY1</b>
	Double male union		Connecting peripheral modules	<b>HMDXX1</b>
	M8 female connector to flying lead - IP67 LED and surge protection		2m Cable	<b>P8LS08L226C</b>
			5m Cable	<b>P8LS08L526C</b>
			9m Cable	<b>P8LS08L926C</b>
	Field wireable connector		M8 Connector	<b>P8CS0803J</b>
			M12 Connector	<b>P8CS1204J</b>

### "S" Series Individual Subbase Valves Size 2 (Valve & Base without Pneumatic Connectors)

	Symbol	Type	Cv	Operator	Part number
		4-way, 2-position	0.8	Single solenoid	<b>P2M2S4ES2C</b>
				Single air pilot	<b>P2M2S4PS</b>
		4-way, 2-position	0.8	Double solenoid	<b>P2M2S4EE2C</b>
				Double air pilot	<b>P2M2S4PP</b>
		3-way, 2-position, dual valve, NC/NC w/ exhaust check	0.44	Double solenoid	<b>P2M2SDEE2C</b>
				Double air pilot	<b>P2M2SDPP</b>
		3-way, 2-position, dual valve, NO/NO w/ exhaust check	0.44	Double solenoid	<b>P2M2SCEE2C</b>
				Double air pilot	<b>P2M2SCPP</b>
		3-way, 2-position, dual valve, NC/NO w/ exhaust check	0.44	Double solenoid	<b>P2M2SEEE2C</b>
				Double solenoid	<b>P2M2SEEE2C</b>
		3-way, 2-position, NC w/ exhaust check	0.44	Single solenoid	<b>P2M2S3ES2C</b>
				Single air pilot	<b>P2M2S3PS</b>
		3-way, 2-position, dual valve, NC/NC	0.44	Double solenoid	<b>P2M2SGEE2C</b>
				Double solenoid	<b>P2M2SGEE2C</b>

### "S" Series Size 2 Accessories

	Description	Tube Size	Option	Part number
	Size 2 push to connect fitting	1/4" OD tube	Elbow	<b>CMD07-2B</b>
			Straight	<b>FMD07-2B</b>
	Size 2 push to connect fitting	3/8" OD tube	Elbow	<b>CMD09-2B</b>
			Straight	<b>FMD09-2B</b>
	Size 2 push to connect fitting	1/2" OD tube	Straight	<b>FMD13-2B</b>
	Size 2 push to connect fitting	6mm OD tube	Elbow	<b>CMD06-2</b>
			Straight	<b>FMD06-2</b>
	Size 2 push to connect fitting	8mm OD tube	Elbow	<b>CMD08-2</b>
			Straight	<b>FMD08-2</b>
	Size 2 push to connect fitting	10mm OD tube	Elbow	<b>CMD10-2</b>
			Straight	<b>FMD10-2</b>
	Size 2 push to connect fitting	12mm OD tube	Elbow	<b>CMD12-2</b>
			Straight	<b>FMD12-2</b>
	Muffler for exhaust port			<b>MMDVA2</b>
	Plug			<b>PMDYY2</b>
	Double male union		Connecting peripheral modules	<b>HMDXX2</b>
	M8 female connector to flying lead - IP67 LED and surge protection		2m Cable	<b>P8LS08L226C</b>
			5m Cable	<b>P8LS08L526C</b>
			9m Cable	<b>P8LS08L926C</b>
	Field wireable connector		M8 Connector	<b>P8CS0803J</b>
			M12 Connector	<b>P8CS1204J</b>

Moduflex Series	Isys Micro Series	Isys ISO Series	Fieldbus	DX ISOMAX Series	Valvair II Series	<b>D</b>	Subbase & Manifold Valve Products
-----------------	-------------------	-----------------	----------	------------------	-------------------	----------	-----------------------------------

**"S" Series Individual Subbase Valve**  
(Complete with Pneumatic and Electrical Connectors)

Moduflex Series	<b>P2M 1 S 4ES 2C 00 A F4</b>							
	<b>Basic series</b>							
	Moduflex P2M							
	<b>Size</b>							
	Size 1 1							
	Size 2 2							
Isys Micro Series	<b>Valve series</b>							
	Individual subbase S							
Isys ISO Series	<b>Valve type / function</b>							
	<b>3-way / 2-position</b>							
	Single solenoid, NC spring return 3ES							
	Single air pilot, NC spring return 3PS							
	<b>4-way / 2-position</b>							
	Single solenoid, spring return 4ES							
	Single air pilot, spring return 4PS							
	Double solenoid 4EE							
	Double air pilot 4PP							
	<b>Dual 3-way, 2-position, spring return</b>							
	Solenoid, NC / NC + PO check (4/3 APB) BEE*							
	Fieldbus Series	Air pilot, NC / NC + PO check (4/3 APB) BPP*						
Solenoid, NO / NO (4/3 Pressure Ctr.) CEE								
Air pilot NO / NO (4/3 Pressure Ctr.) CPP								
<b>Solenoid, NC / NC with exhaust check DEE</b>								
Air pilot, NC / NC with exhaust check DPP								
Solenoid, NO / NC with exhaust check EEE								
Solenoid, NC / NC without check (4/3 Exh. Ctr.) GEE								
<b>Operator voltage</b>								
24VDC 2C								
Remote pilot - 5/32" (4mm) Tube 00								
DX ISOMAX Series		<b>Ports (all ports)</b>						
	C0* 10mm Elbow fitting							
	C2* 12mm Elbow fitting							
	<b>C4 5/32" (4mm) Elbow fitting</b>							
	C6 6mm Elbow fitting							
	<b>C7 1/4" Elbow fitting</b>							
	C8* 8mm Elbow fitting							
	<b>C9* 3/8" Elbow fitting</b>							
	F0* 10mm Straight fitting							
	F2* 12mm Straight fitting							
	<b>F3* 1/2" Straight fitting</b>							
	Valvair II Series	<b>F4 5/32" (4mm) Straight fitting</b>						
F6 6mm Straight fitting								
<b>F7 1/4" Straight fitting</b>								
F8* 8mm Straight fitting								
<b>F9* 3/8" Straight fitting</b>								
<b>Fitting configuration</b>								
<b>A* Straight fittings</b>								
<b>B* Elbow fittings</b>								
<b>C*† Straight fitting &amp; muffler</b>								
<b>D*† Elbow fitting &amp; muffler</b>								
<b>LED / Cable</b>								
<b>00 No cable, no LED, no surge suppression</b>								
<b>V2 2 Meter cable with LED and surge suppression</b>								
V5 5 Meter cable with LED and surge suppression								
V9 9 Meter cable with LED and surge suppression								

\* Only available with size 2 valves.

Example for fitting configuration:  
Size 1  
CF7 Ports 1 & 3  
1/4" straight fitting & muffler  
Ports 2 & 4  
1/4" straight fittings  
Size 2  
AC0 Ports 1 & 3  
10mm elbow fittings  
Ports 2 & 4  
10mm elbow fittings


\* Valve includes peripheral P. O. Check Valve and union fittings.

**With only one universal solenoid pilot for all configurations**

















24VDC is now a global standard for all machines.

The Moduflex 24VDC unique solenoid pilot is supplied with the multi-function manual override that can be adapted to all requirements, as explained by the drawings.










**Multi-function adaptable manual override**



## "T" Series Manifold Valves with Individual Connectors Size 1

	Symbol	Type	Cv	Operator	Part number
		4-way, 2-position	0.32	Single solenoid	<b>P2M1T4ES2C</b>
				Single air pilot	<b>P2M1T4PS</b>
		4-way, 2-position	0.32	Double solenoid	<b>P2M1T4EE2C</b>
				Double air pilot	<b>P2M1T4PP</b>
		4-way, 2-position, dual valve w/ exhaust check	0.18	Double solenoid	<b>P2M1TJEE2C</b>
				Double air pilot	<b>P2M1TJPP</b>
		3-way, 2-position, dual valve, NC/NC w/ exhaust check	0.22	Double solenoid	<b>P2M1TDEE2C</b>
				Double air pilot	<b>P2M1TDPP</b>
		3-way, 2-position, dual valve, NO/NO w/ exhaust check	0.22	Double solenoid	<b>P2M1TCEE2C</b>
				Double air pilot	<b>P2M1TCPP</b>
		3-way, 2-position, dual valve, NC/NO w/ exhaust check	0.22	Double solenoid	<b>P2M1TEEE2C</b>
				Double solenoid	<b>P2M1TEEE2C</b>
		3-way, 2-position, NC w/ exhaust check	0.22	Single solenoid	<b>P2M1T3ES2C</b>
				Single air pilot	<b>P2M1T3PS</b>
		3-way, 2-position, dual valve, NC/NC	0.22	Double solenoid	<b>P2M1TGEE2C</b>

## "T" Series Size 1 Accessories

	Description	Tube size	Option	Part number
	Size 1 push to connect fitting	5/32" or 4mm	Elbow	<b>CMD04-1</b>
			Straight	<b>FMD04-1</b>
	Size 1 push to connect fitting	1/4"	Elbow	<b>CMD07-1B</b>
			Straight	<b>FMD07-1B</b>
	Size 1 push to connect fitting	6mm	Elbow	<b>CMD06-1</b>
			Straight	<b>FMD06-1</b>
	Muffler for exhaust port			<b>MMDVA1</b>
	Plug			<b>PMDYY1</b>
	Double male union		Connecting peripheral modules	<b>HMDXX1</b>
	M8 female connector to flying lead - IP67 LED and surge protection		2M cable	<b>P8LS08L226C</b>
			5M cable	<b>P8LS08L526C</b>
			9M cable	<b>P8LS08L926C</b>
	Field wireable connector		M8 connector	<b>P8CS0803J</b>
			M12 connector	<b>P8CS1204J</b>
	Torx screwdriver			<b>P2M1K0TASD</b>


## Manifold Options

Module	Part number
Pneumatic end plate kit	<b>P2M2HXT01*</b>
Pneumatic end plate kit with torx screwdriver	<b>P2M2HXT0T*</b>
Intermediate supply module (Includes 4 configuration plates)	<b>P2M2BXT0A*</b>

\* Use Fittings for Size 2 Modules Only















P2M2HXT01









P2M2BXT0A

## "T" Series Manifold Valves with Individual Connectors Size 2

		Symbol	Type	Cv	Operator	Part number
Moduflex Series			4-way, 2-position	0.8	Single solenoid	<b>P2M2T4ES2C</b>
					Single air pilot	<b>P2M2T4PS</b>
			4-way, 2-position	0.8	Double solenoid	<b>P2M2T4EE2C</b>
					Double air pilot	<b>P2M2T4PP</b>
			3-way, 2-position, dual valve, NC/NC w/ exhaust check	0.44	Double solenoid	<b>P2M2TDEE2C</b>
					Double air pilot	<b>P2M2TDPP</b>
Isys Micro Series			3-way, 2-position, dual valve, NO/NO w/ exhaust check	0.44	Double solenoid	<b>P2M2TCEE2C</b>
					Double air pilot	<b>P2M2TCPP</b>
Isys ISO Series			3-way, 2-position, dual valve, NC/NO w/ exhaust check	0.44	Double solenoid	<b>P2M2TEEE2C</b>
					Single solenoid	<b>P2M2T3ES2C</b>
			3-way, 2-position, dual valve, NC/NC w/ exhaust check	0.44	Single air pilot	<b>P2M2T3PS</b>
					Double solenoid	<b>P2M2TGEE2C</b>

## "T" Series Size 2 Accessories

		Description	Tube size	Option	Part number
Fieldbus Series		Size 2 push to connect fitting	1/4"	Elbow	<b>CMD07-2B</b>
				Straight	<b>FMD07-2B</b>
		Size 2 push to connect fitting	3/8"	Elbow	<b>CMD09-2B</b>
				Straight	<b>FMD09-2B</b>
		Size 2 push to connect fitting	1/2"	Straight	<b>FMD13-2B</b>
				Straight	<b>FMD13-2B</b>
DX ISOMAX Series		Size 2 push to connect fitting	6mm	Elbow	<b>CMD06-2</b>
				Straight	<b>FMD06-2</b>
		Size 2 push to connect fitting	8mm	Elbow	<b>CMD08-2</b>
				Straight	<b>FMD08-2</b>
		Size 2 push to connect fitting	10mm	Elbow	<b>CMD10-2</b>
				Straight	<b>FMD10-2</b>
Valvair II Series		Size 2 push to connect fitting	12mm	Elbow	<b>CMD12-2</b>
				Straight	<b>FMD12-2</b>
		Size 2 Push to connect fitting	12mm	Elbow	<b>CMD12-2</b>
				Straight	<b>FMD12-2</b>
		Size 2 Push to connect fitting	12mm	Elbow	<b>CMD12-2</b>
				Straight	<b>FMD12-2</b>
D Series		Muffler for exhaust port			<b>MMDVA2</b>
		Plug			<b>PMDYY2</b>
		Double male union		Connecting peripheral modules	<b>HMDXX2</b>
		M8 female connector to flying lead - IP67 LED and surge protection		2M cable	<b>P8LS08L226C</b>
				5M cable	<b>P8LS08L526C</b>
				9M cable	<b>P8LS08L926C</b>
Subbase & Manifold Valve Products		Field wireable connector		M8 connector	<b>P8CS0803J</b>
				M12 connector	<b>P8CS1204J</b>
Subbase & Manifold Valve Products		Torx screwdriver			<b>P2M1K0TASD</b>


## Manifold Options

Module	Part number
Pneumatic end plate kit	<b>P2M2HXT01*</b>
Pneumatic end plate kit with torx screwdriver	<b>P2M2HXT0T*</b>
Intermediate supply module (Includes 4 configuration plates)	<b>P2M2BXT0A*</b>

\* Use Fittings for Size 2 Modules Only



P2M2HXT01



P2M2BXT0A

## "T" Series Valve Manifold with Individual Connectors (Complete with Pneumatic and Electrical Connectors)

**P2M 1 T 4ES 2C 00 0 F4**

Basic series	
Valvetronic modules	P2M

Size	
Size 1	1
Size 2	2

Valve series	
Individual wire	T

Valve type / function	
<b>3-way / 2-position</b>	
Single solenoid, NC spring return	3ES
Single air pilot, NC spring return	3PS
<b>4-way / 2-position</b>	
Single solenoid, spring return	4ES
Single air pilot, spring return	4PS
Double solenoid	4EE
Double air pilot	4PP
<b>Dual 3-way, 2-position, spring return</b>	
Solenoid, NC / NC + PO check (4/3 APB)	BEE*
Air pilot, NC / NC + PO check (4/3 APB)	BPP*
Solenoid, NO / NO (4/3 Pressure Ctr.)	CEE
Air pilot NO / NO (4/3 Pressure Ctr.)	CPP
Solenoid, NC / NC with exhaust check	DEE
Air pilot, NC / NC with exhaust check	DPP
Solenoid, NO / NC with exhaust check	EEE
Solenoid, NC / NC without check (4/3 Exh. Ctr.)	GEE
<b>Dual 4-way, 2-position, Spring Return</b>	
Solenoid	JEE**
Air pilot	JPP**

\* Valve includes peripheral P. O. check valve and union fittings.  
\*\* Size 1 only.

Ports 2 & 4	
C0*	10mm Elbow fitting
C2*	12mm Elbow fitting
C4	5/32" (4mm) Elbow fitting
C6	6mm Elbow fitting
C7	1/4" Elbow fitting
C8*	8mm Elbow fitting
C9*	3/8" Elbow fitting
F0*	10mm Straight fitting
F2*	12mm Straight fitting
F3*	1/2" Straight fitting
F4	5/32" (4mm) Straight fitting
F6	6mm Straight fitting
F7	1/4" Straight fitting
F8*	8mm Straight fitting
F9*	3/8" Straight fitting

\* Only available with size 2 valves.

Ports 1 & 3	
0	None

Led / Cable	
00	No cable, no led, no surge suppression
V2	2 Meter cable with led and surge suppression
V5	5 Meter cable with led and surge suppression
V9	9 Meter cable with led and surge suppression


Operator Voltage	
2C	24VDC
00	Remote pilot - 5/32" (4mm) tube

### With only one universal solenoid pilot for all configurations

24VDC is now a global standard for all machines.










The Moduflex 24VDC unique solenoid pilot is supplied with the multi-function manual override that can be adapted to all requirements, as explained by the drawings.

### Multi-function adaptable manual override















## "V" Series Manifold Valves with Collective Wiring Size 1

	Symbol	Type	Cv	Operator	Part number
<div> Single Solenoid</div> <div> Double Solenoid</div>		4-way, 2-position	0.32	Single solenoid	<b>P2M1V4ES2CV</b>
		4-way, 2-position	0.32	Double solenoid	<b>P2M1V4EE2CV</b>
		4-way, 2-position, dual valve, w/ exhaust check	0.18		<b>P2M1VJEE2CV</b>
		3-way, 2-position, dual valve, NC/NC w/ exhaust check	0.22	Double solenoid	<b>P2M1VDEE2CV</b>
		3-way, 2-position, dual valve, NO/NO w/ exhaust check	0.22	Double solenoid	<b>P2M1VCEE2CV</b>
		3-way, 2-position, dual valve, NC/NO w/ exhaust check	0.22	Double solenoid	<b>P2M1VEEE2CV</b>
		3-way, 2-position, NC w/ exhaust check	0.22	Single solenoid	<b>P2M1V3ES2CV</b>
		3-way, 2-position, dual valve, NC/NC	0.22	Double solenoid	<b>P2M1VGEE2CV</b>

## "V" Series Size 1 Accessories

	Description	Tube size	Option	Part number
   	Size 1 push to connect fitting	5/32"	Elbow	<b>CMD04-1</b>
			Straight	<b>FMD04-1</b>
	Size 1 push to connect fitting	1/4"	Elbow	<b>CMD07-1B</b>
			Straight	<b>FMD07-1B</b>
	Size 1 push to connect fitting	6mm	Elbow	<b>CMD06-1</b>
			Straight	<b>FMD06-1</b>
     	Muffler for exhaust port			<b>MMDVA1</b>
	Plug			<b>PMDYY1</b>
	Double male union		Connecting peripheral modules	<b>HMDXX1</b>
	Electrical 20-pin multi-connector cable with flying leads	IP65 rated	2M cable	<b>P8LMH20M2A</b>
			5M cable	<b>P8LMH20M5A</b>
			9M cable	<b>P8LMH20M9A</b>
	Electrical 25-pin D-sub cable	IP20 rated	3M cable	<b>P8LMH25M3A</b>
			9M cable	<b>SCD259D</b>
		IP65 rated	3M cable	<b>SCD253W</b>
			9M cable	<b>SCD259WE</b>
	Field wireable connector for power supply	Female	M12 - A code	<b>P8CS1205AA</b>
	Line termination resistor	Profibus DP	M12 type B	<b>P8BPA00MB</b>
		Devicenet or Canopen	M12 type A	<b>P8BPA00MA</b>
	AS-i M12 cable with jack for addressing		1M cable	<b>P8LS12JACK</b>
	Torx screwdriver			<b>P2M1K0TASD</b>

## Electrical Connections

Description	Part number
20-pin, Multi-connector electrical head module	<b>P2M2HEV0A</b>
25-pin, D-sub, electrical head module	<b>P2M2HEV0D</b>

## Fieldbus Connections

Description			Part number
Profibus DP			P2M2HBVP21600
DeviceNet			P2M2HBVD21600
CANopen			P2M2HBVC21600
Interbus S			P2M2HBVS11600
AS-i	0 inputs and 8 solenoid outputs		P2M2HBVA10800
AS-i	8 (PNP) inputs on eight (M8) connectors and 8 solenoid outputs		P2M2HBVA10808A
AS-i	8 (PNP) inputs on four (M12) connectors and 8 solenoid outputs		P2M2HBVA10808B
AS-i Version 2.1 Protocol	AS-i 0 inputs and 6 solenoid outputs		P2M2HBVA20600
AS-i Version 2.1 Protocol	AS-i 8 (PNP) inputs on eight (M8) connectors and 6 solenoid outputs		P2M2HBVA20608A
AS-i Version 2.1 Protocol	AS-i 8 (PNP) inputs on four (M12) connectors and 6 solenoid outputs		P2M2HBVA20608B

## Manifold Options

Module	Part number
Pneumatic end plate kit	<b>P2M2HXT01*</b>
Pneumatic end plate kit with torx screwdriver	<b>P2M2HXT0T*</b>
Intermediate supply module (Includes 4 configuration plates)	<b>P2M2BXV0A*</b>

\* Use Fittings for Size 2 Modules Only



P2M2HXT01



P2M2BXV0A

Moduflex  
Series

Isys Micro  
Series

Isys ISO  
Series

Fieldbus

DX ISOMAX  
Series










Valvair II  
Series

**D**









Subbase & Manifold  
Valve Products



## "V" Series Manifold Valves with Collective Wiring Size 2

	Symbol	Type	Cv	Operator	Part number
  <p>Single Solenoid</p> <p>Double Solenoid</p>		4-way, 2-position	0.8	Single solenoid	<b>P2M2V4ES2CV</b>
		4-way, 2-position	0.8	Double solenoid	<b>P2M2V4EE2CV</b>
		3-way, 2-position, dual valve, NC/NC w/ exhaust check	0.44	Double solenoid	<b>P2M2VDEE2CV</b>
		3-way, 2-position, dual valve, NO/NO w/ exhaust check	0.44	Double solenoid	<b>P2M2VCEE2CV</b>
		3-way, 2-position, dual valve, NC/NO w/ exhaust check	0.44	Double solenoid	<b>P2M2VEEE2CV</b>
		3-way, 2-position, NC w/ exhaust check	0.44	Single solenoid	<b>P2M2V3ES2CV</b>
		3-way, 2-position, dual valve, NC/NC	0.44	Double solenoid	<b>P2M2VGEE2CV</b>

## "V" Series Size 2 Accessories

	Description	Tube size	Option	Part number
 	Size 2 push to connect fitting	1/4" OD tube	Elbow	<b>CMD07-2B</b>
			Straight	<b>FMD07-2B</b>
	Size 2 push to connect fitting	3/8" OD tube	Elbow	<b>CMD09-2B</b>
			Straight	<b>FMD09-2B</b>
	Size 2 push to connect fitting	1/2" OD tube	Straight	<b>FMD13-2B</b>
	Size 2 push to connect fitting	6mm OD tube	Elbow	<b>CMD06-2</b>
			Straight	<b>FMD06-2</b>
	Size 2 push to connect fitting	8mm OD tube	Elbow	<b>CMD08-2</b>
			Straight	<b>FMD08-2</b>
	Size 2 push to connect fitting	10mm OD tube	Elbow	<b>CMD10-2</b>
			Straight	<b>FMD10-2</b>
	Size 2 push to connect fitting	12mm OD tube	Elbow	<b>CMD12-2</b>
			Straight	<b>FMD12-2</b>
     	Muffler for exhaust port			<b>MMDVA2</b>
	Plug			<b>PMDYY2</b>
	Double Male Union		Connecting peripheral modules	<b>HMDXX2</b>
	Electrical 20-pin multi-connector cable with flying leads	IP65 rated	2M cable	<b>P8LMH20M2A</b>
			5M cable	<b>P8LMH20M5A</b>
			9M cable	<b>P8LMH20M9A</b>
	Electrical 25-pin D-sub cable	IP20 rated	3M cable	<b>P8LMH25M3A</b>
			9M cable	<b>SCD259D</b>
		IP65 rated	3M cable	<b>SCD253W</b>
			9M cable	<b>SCD259WE</b>
	Torx screwdriver			<b>P2M1K0TASD</b>