

Rittal – The System.

Faster – better – everywhere.

▶ TS punched section with mounting flange, 17 x 73 mm – TS 8612.050

Date : Apr 17, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TS punched section with mounting flange, 17 x 73 mm – TS 8612.050

created: 17.04.2020 build on www.rittal.com/uk-en



Product description

Design:	For the inner mounting level and for mounting on doors
Description:	Variable, with 5 rows of holes for universal skeleton structures or partial assembly. Simply locate onto the TS punchings and secure.
Material:	Sheet steel
Surface finish:	Zinc-plated
Assembly instruction:	The rail for internal mounting is required when installing in CM, TP
Supply includes:	Assembly screws

Product features

To fit:	Width/depth: 500 mm
Dimensions:	Length: 490 mm
Installation options:	On the vertical TS enclosure section: On the inner mounting level, height-offset all-round For SE, may additionally be mounted on the top horizontal section in the depth In the tubular door frame for TS, SE and PC In CM and TP via rail for interior installation: In the width, for inner mounting level As a mounting kit for component shelves, simply locate and secure. One pack is sufficient for 2 component shelves. 100 kg surface load, static
To fit door width:	600 mm

Packs of:	4 pc(s).
Weight/pack:	2.26 kg
Copper weight (kg per piece):	0
EAN:	4028177212084
Customs tariff number:	73269098
ETIM 7.0:	EC002625
ETIM 6.0:	EC002625
eCl@ss 8.0/8.1:	27189234
eCl@ss 6.0/6.1:	23159101
Product description:	TS TS punched section with mounting flange, 17 x 73 mm, for inner mounting level: for W/D: 500 mm, for door width: 600 mm, L: 490 mm
Approvals	
Certificates:	EAC