


Ordinateur embarqué > Ordinateur à carte unique > ETX / COM EXPRESS / Q7

IEM-LX-800

AMD Geode™ LX 800 Highly Integrated ETX Module



Features

AMD Geode™ LX 800 Highly Integrated ETX Module

Specifications

System	CPU
Chipset	AMD Geode? LX 800 + AMD CS5536
Memory Max.	One 200-pin 400/333 MHz DDR SDRAM SO-DIMM Supported (system max. 1GB)
I/O Interface	Ethernet
Digital I/O	N/A
Display	VGA integrated in AMD Geode? LX 800 24-bit TTL (optional) 18-bit single-channel LVDS
Audio	Realtek ALC203 AC'97 codec
Expansion	4 x PCI bus master ISA support by ITE IT8888G
I/O Interface	4 x USB 2.0 2 x RS-232 1 x IDE 1 x LPT/FDD 1 x PS/2 KB/MS
Power	Power consumption
Environment	Operating Temperature
Humidity	5% ~ 95%, non-condensing
Watchdog Timer	Watchdog Timer
Super IO	Super IO
I/O Interface	I/O Interface
1 x LPT	
2 x RS-232	

Ordering Information

IEM-LX-800-R11	AMD LX800 500MHz processor,VGA/LVDS/TTL,LAN & Audio,RoHS
----------------	--