## Rittal - The System.

Faster – better – everywhere.

Roof-mounted fan, roof vent – SK 3149.007

Date: May 24, 2018



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

## Roof-mounted fan, roof vent – SK 3149.007

created: 24.05.2018 build on www.rittal.com/us-en



## Discontinued article.

This item will be discontinued on: 30.04.2017 |||This item is being replaced by: 3139100

Product description	
Version:	Unit ready for connection with built-in radial fan
Material:	Carbon steel, spray finished
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 43
Supply includes:	Sealing and assembly components Drilling template Connection cable (3 m)
Note:	Via additional installation of the filter holder with filter mat, a protection category of IP 44 is achieved with roof vent 3148.007.
Product features	
Air throughput (unimpeded air flow):	360 m³/h (211.9 cfm)
Unimpeded air flow (without filter mats):	
Unimpeded air flow (with filter mats):	
Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Height: 95 mm (3.7 ") Width: 420 mm (17 ")

© Rittal 2018

Depth: 340 mm (13 ")

Required mounting cut-out:

Width: 345 mm (14 ") Depth: 265 mm (10 ")

**Temperature range:** Operation (environment): -10°C...+60°C

Rated power Pel: At 50 Hz: 42 W

Rated current (max.): At 50 Hz: 0.2 A

Noise pressure level: At 50 Hz: 53 dB(A)

Packaging unit: 1 pc(s).

Weight/packaging unit:

7.8 kg

**EAN:** 4028177165342

Customs tariff number:

84145915

**ETIM 6.0:** EC000320

**ETIM 5.0:** EC000320

**eCl@ss 8.0/8.1**: 27180716

**e Cl@ss 7.0/7.1**: 27180716

**eCl@ss 6.0/6.1**: 27180716

eCl@ss 5.1/5.1.4: 27180707

Product description (long):

SK Roof-mounted fan, 360 m³/h, 230 V, 1~, 50/60 Hz, WHD: 420x95x340 mm

**Approvals** 

© Rittal 2018

Approvals: Approval overview

Certificates: EAC

**Declarations:** Declaration of conformity Manufacturer's declaration

2