

Spare part SIMATIC S7-300, CPU 315-2DP Central processing unit with MPI Integr. power supply 24 V DC Work memory 128 KB 2nd interface DP master/slave Micro Memory Card required



General information	
HW functional status	01
Firmware version	V2.6
Engineering with	
<ul style="list-style-type: none"> Programming package 	STEP 7 V5.2 + SP1 or higher with HW update
Supply voltage	
Rated value (DC)	Yes
<ul style="list-style-type: none"> 24 V DC 	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2 A min.
Input current	
Current consumption (rated value)	0.8 A
Current consumption (in no-load operation), typ.	60 mA
Inrush current, typ.	2.5 A
I^2t	0.5 A ² ·s
Power loss	

Power loss, typ.	2.5 W
Memory	
Work memory	
<ul style="list-style-type: none"> integrated 	128 kbyte; For program and data
<ul style="list-style-type: none"> expandable 	No
Load memory	
<ul style="list-style-type: none"> Plug-in (MMC) 	Yes
<ul style="list-style-type: none"> Plug-in (MMC), max. 	8 Mbyte
<ul style="list-style-type: none"> Data management on MMC (after last programming), min. 	10 y
Backup	
<ul style="list-style-type: none"> present 	Yes; Guaranteed by MMC (maintenance-free)
<ul style="list-style-type: none"> without battery 	Yes; Program and data
CPU processing times	
for bit operations, typ.	0.1 μ s
for word operations, typ.	0.2 μ s
for fixed point arithmetic, typ.	2 μ s
for floating point arithmetic, typ.	3 μ s
CPU-blocks	
Number of blocks (total)	1 024; (DBs, FCs, FBs OBs, SDBs); the maximum number of loadable blocks can be reduced by the MMC being used.
DB	
<ul style="list-style-type: none"> Number, max. 	1 023; Number band: 1 to 1023
<ul style="list-style-type: none"> Size, max. 	16 kbyte
FB	
<ul style="list-style-type: none"> Number, max. 	1 024; Number range: 0 to 2047
<ul style="list-style-type: none"> Size, max. 	16 kbyte
FC	
<ul style="list-style-type: none"> Number, max. 	1 024; Number range: 0 to 2047
<ul style="list-style-type: none"> Size, max. 	16 kbyte
OB	
<ul style="list-style-type: none"> Size, max. 	16 kbyte
<ul style="list-style-type: none"> Number of free cycle OBs 	1; OB 1
<ul style="list-style-type: none"> Number of time alarm OBs 	1; OB 10
<ul style="list-style-type: none"> Number of delay alarm OBs 	1; OB 20
<ul style="list-style-type: none"> Number of cyclic interrupt OBs 	1; OB 35
<ul style="list-style-type: none"> Number of process alarm OBs 	1; OB 40
<ul style="list-style-type: none"> Number of DPV1 alarm OBs 	3; OB 55, 56, 57
<ul style="list-style-type: none"> Number of startup OBs 	1; OB 100
<ul style="list-style-type: none"> Number of asynchronous error OBs 	1; OB 80
<ul style="list-style-type: none"> Number of synchronous error OBs 	2; OB 121, 122

Nesting depth	
• per priority class	8
• additional within an error OB	4
Counters, timers and their retentivity	
S7 counter	
• Number	256
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	8
Counting range	
— adjustable	Yes
— lower limit	0
— upper limit	999
IEC counter	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
S7 times	
• Number	256
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	No retentivity
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
retentive data area in total	all
Flag	
• Number, max.	2 048 byte
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Data blocks	
• Retentivity adjustable	Yes; via non-retain property on DB

• Retentivity preset	Yes
Address area	
I/O address area	
• Inputs	2 kbyte
• Outputs	2 kbyte
Process image	
• Inputs	128 byte
• Outputs	128 byte
Digital channels	
• Inputs	16 384
— of which central	1 024
• Outputs	16 384
— of which central	1 024
Analog channels	
• Inputs	1 024
— of which central	256
• Outputs	1 024
— of which central	256
Hardware configuration	
Number of expansion units, max.	3
Number of DP masters	
• integrated	1
• via CP	4
Number of operable FMs and CPs (recommended)	
• FM	8
• CP, PtP	8
• CP, LAN	10
Rack	
• Racks, max.	4
• Modules per rack, max.	8
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Backup time	6 wk; At 40 °C ambient temperature
• Deviation per day, max.	10 s
Operating hours counter	
• Number	1
• Number/Number range	0
• Range of values	0 to 2 ³¹ hours (when using SFC 101)

• Granularity	1 h
• retentive	Yes; Must be restarted at each restart
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• in AS, master	Yes
• in AS, slave	No
Digital inputs	
integrated channels (DI)	0
Digital outputs	
integrated channels (DO)	0
Analog inputs	
integrated channels (AI)	0
Analog outputs	
integrated channels (AO)	0
Interfaces	
Number of industrial Ethernet interfaces	0
Number of PROFINET interfaces	0
Number of RS 485 interfaces	1
Number of RS 422 interfaces	0
1. Interface	
Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	No
Power supply to interface (15 to 30 V DC), max.	200 mA
Protocols	
• MPI	Yes
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Point-to-point connection	No
MPI	
• Number of connections	16
• Transmission rate, max.	187.5 kbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes

— S7 communication, as client	No
— S7 communication, as server	Yes

2. Interface

Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	200 mA
Protocols	
• MPI	No
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
• Point-to-point connection	No
PROFIBUS DP master	
• Number of connections, max.	16
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	124; Per station
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	Yes; I blocks only
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
— Equidistance	Yes
— Isochronous mode	No
— SYNC/FREEZE	Yes
— DPV1	Yes
Address area	
— Inputs, max.	2 048 byte
— Outputs, max.	2 048 byte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
PROFIBUS DP slave	
• Number of connections	16
• GSD file	The latest GSD file is available at: http://www.siemens.com/profibus-gsd
• Transmission rate, max.	12 Mbit/s
• automatic baud rate search	Yes; only with passive interface
• Address area, max.	32

• User data per address area, max.	32 byte
Services	
— PG/OP communication	Yes
— Routing	Yes; with interface active
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV1	No
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
Communication functions	
PG/OP communication	Yes
Global data communication	
• supported	Yes
• Number of GD loops, max.	8
• Number of GD packets, max.	8
• Number of GD packets, transmitter, max.	8
• Number of GD packets, receiver, max.	8
• Size of GD packets, max.	22 byte
• Size of GD packet (of which consistent), max.	22 byte
S7 basic communication	
• supported	Yes
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes; Via CP and loadable FB
• User data per job, max.	180 byte; With PUT/GET
• User data per job (of which consistent), max.	64 byte; as server
S5 compatible communication	
• supported	Yes; via CP and loadable FC
Number of connections	
• overall	16
• usable for PG communication	15

— reserved for PG communication	1
— adjustable for PG communication, min.	1
— adjustable for PG communication, max.	15
• usable for OP communication	15
— reserved for OP communication	1
— adjustable for OP communication, min.	1
— adjustable for OP communication, max.	15
• usable for S7 basic communication	12
— reserved for S7 basic communication	0
— adjustable for S7 basic communication, min.	0
— adjustable for S7 basic communication, max.	12
• usable for routing	4

S7 message functions

Number of login stations for message functions, max.	16; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	40

Test commissioning functions

Status block	Yes
Single step	Yes
Number of breakpoints	2
Status/control	
• Status/control variable	Yes
• Variables	Inputs, outputs, memory bits, DB, times, counters
• Number of variables, max.	30
— of which status variables, max.	30
— of which control variables, max.	14
Forcing	
• Forcing	Yes
• Forcing, variables	Inputs, outputs
• Number of variables, max.	10
Diagnostic buffer	
• present	Yes
• Number of entries, max.	100
— adjustable	No

Configuration

Configuration software	
• STEP 7	Yes; V5.2 SP1 or higher with HW update
Programming	

- Command set see instruction list
- Nesting levels 8
- System functions (SFC) see instruction list
- System function blocks (SFB) see instruction list

Programming language

- LAD Yes
- FBD Yes
- STL Yes
- SCL Yes
- CFC Yes
- GRAPH Yes
- HiGraph® Yes

Know-how protection

- User program protection/password protection Yes

Dimensions

Width	40 mm
Height	125 mm
Depth	130 mm

Weights

Weight, approx.	290 g
-----------------	-------

last modified: 05/09/2020