

Product data sheet

Specifications



glass fibre optic for sensor - thru-beam - straight - metal - 2m - Sn200mm

XUYFVERMD201

❗ Discontinued on: 08 December 2020

❗ Discontinued

Main

Range of product	Telemecanique Photoelectric sensors XU
Sensor name	XUY
Sensor design	Fiber design
Sheath type	Metal reinforced
[Sn] nominal sensing distance	200 mm XUYAFV
End fitting type	Straight with nickel plated brass, M4 x 0.7

Complementary

Electronic sensor type	Photo-electric sensor
Optic fiber material	50 μ glass
Sheath material	Spiraled metal + polyolefine
Detection system	Thru beam
Optic fiber length	2 m
Minimum bending radius	20 mm
Head mounting	M4 x 0.7

Environment

Ambient air temperature for operation	-25...120 °C
---------------------------------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17 cm
Package 1 Width	1.5 cm
Package 1 Length	17 cm
Package 1 Weight	103 g

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
-------------------	--

Mercury free	Yes
---------------------	-----

RoHS exemption information	Yes
-----------------------------------	-----


California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
----------------------------------	---

Contractual warranty

Warranty	18 months
-----------------	-----------

Recommended replacement(s)

XUYFVERMD201 is replaced by the following product range:



Photoelectric sensors XU
Photo-electric sensors
Products: 703