



Main

| | |
|------------------|--|
| Range of Product | Telemecanique Inductive proximity sensors XS |
| Series name | General purpose |
| Sensor Type | Inductive proximity sensor |
| Sensor name | XSC |

Complementary

| | |
|---------------------------------------|--|
| Body type | Fixed |
| Type of output signal | Discrete |
| Wiring Technique | 2-wire |
| Electrical connection | Screw-clamp terminals |
| Cable entry | 1 entry tapped for Pg 13.5 cable gland |
| Product Certifications | CCC |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| IP degree of protection | IP67 |

Ordering and shipping details

| | |
|-------------------|--------------------------|
| Category | 22486-SENSORS, PROXIMITY |
| Discount Schedule | DS2 |
| GTIN | 00785901100591 |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|------------------------------|-----|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.