

UR67-MP-HP-16DI-12-60M

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



More performance. Simplified.

u-remote.

Weidmüller u-remote – our innovative remote I/O concept with IP 67 which focuses purely on user benefits: tailored planning, faster installation, safer start-up, no more downtime. For considerably improved performance and greater productivity.

u-remote stands for "More Performance". Simplified

General ordering data

Version	Automation Products - u-remote IP67, Sensor-actuator active distributor, PROFINET V2.3, EtherNet/IP, EtherCAT, Multiprotocol
Order No.	2426270000
Type	UR67-MP-HP-16DI-12-60M
GTIN (EAN)	4050118434422
Qty.	1 pc(s).

Creation date March 26, 2021 11:10:19 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

UR67-MP-HP-16DI-12-60M

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Height	17.6 mm	Height (inches)	0.693 inch
Length	200 mm	Length (inches)	7.874 inch
Net weight	500 g	Width	59.6 mm
Width (inches)	2.346 inch		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Connections

Fieldbus (BUS-IN)	1x M12 female 4-pole, D-coded	Fieldbus (BUS-OUT)	1x M12 female 4-pole, D-coded
I/O connections	8 x M12 socket 5-pole, A-coded	Supply voltage (AUX-IN)	1x M12 plug 5-pole, L-coded
Supply voltage (AUX-OUT)	1x M12 socket 5-pole, L-coded		

Digital inputs

Diagnostic display	Per channel, via LED, red		
Digital inputs	Short-circuit protection	Yes	
	Overload protection	Yes	
	Reverse polarity protection	Yes	
Input current, high	Type 1 in acc. with IEC 61131-2		
Input current, low	Type 1 in acc. with IEC 61131-2		
Status indicator	Per channel, via LED, yellow		

General data

Housing main material	Zinc diecast	Module variants	16 digital inputs
Protection degree	IP67	UL 94 flammability rating	UL 94

Supply voltage

Limits	18 V DC ... 30 V DC	Operating voltage	24 V
Power consumption of module electronics	100 mA typical	Reverse polarity protection	Yes

Classifications

ETIM 6.0	EC001597	ETIM 7.0	EC001597
ECLASS 9.0	27-24-26-02	ECLASS 9.1	27-24-26-02
ECLASS 10.0	27-24-26-02	ECLASS 11.0	27-24-26-02

Approvals

Approvals



ROHS	Conform
UL File Number Search	E141197

Creation date March 26, 2021 11:10:19 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

2

UR67-MP-HP-16DI-12-60M

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data**Downloads**

Approval/Certificate/Document of Conformity	UR67_EU Declaration of Conformity PN45
Engineering Data	STEP
Engineering Data	EPLAN, WSCAD
Software	UR67 - GSDML V2.33 / EDS V3.21 / ESI V1.2 files UR67 - GSDML V2.31 / EDS V3.9 / ESI V1.2 files
User Documentation	MAN UR67 MP DE MAN UR67 MP EN