

192G1004

Analog voltmeter D48A90-V DIN 48x48 0-250V



Ferromagnetic voltmeters measure the AC voltage of any electrical circuit. They are embedded in the front panel of cabinets, enclosures or other equipment.

Strong points

- Extensive range
- Made in Europe
- Many accessories

General characteristics

- Deflection: 90°.
- Insulating voltage: 660 V.
- Dielectric quality 2 kV - 50 Hz - 1 mn.
- Consumption: 3 VA.
- Operating frequency: 45/65 Hz.
- Connection: screw or FASTON lugs.

Compliance with standards

- IEC 60051-1
- IEC 60414
- NF EN 60051-1
- DIN 43780
- NF C 42-010
- VDE 0410
- BS 5448
- BS 89

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/192G1004>

----- System -----

Fill rate E-Order Common	33
Fill rate E-Order Selection	50

Classification

UNSPSC	41113637
ETIM Class	EC002306
IGCC	6303

Commerce

Effective date	1998-02-09
Country of origin	ES
Discount Policy	1EC10
Discount Policy Label	ANALOG INDICATORS

ETIM - Electrical characteristics

Measuring range [V]	250..250
Accuracy class	1.5
Power loss [W]	3
Calibrated	Yes
Voltage type	AC

ETIM - Mechanical characteristics

Transformer connection	No
Modular version	Yes
Width [mm]	48
Height [mm]	48

ETIM - Technical features

Model	DIN rail
Max. needle deflection [°]	90
Scales lighting	No

Logistics

GTIN/EAN	3596031084081
Customs number	9030337000
Price unit	PC
Weight of the packing unit	0.119
Length of the packing unit	0.06
Width of the packing unit	0.07
Depth of the packing unit	0.09

Technical Characteristics

Rated voltage	0..250 VAC
Scale nominal value	90°
Type	D48x48