

# Product datasheet

Specifications



extension ETL - 2P - 1C/O + 1NO -  
16A - coil 110 VDC - 230...240VAC  
50/60Hz

15530

! Discontinued on: 01 April 2019

! Discontinued

EAN Code : 3303430155300

## Main

Product or component type	Extension for impulse relay
Device short name	ETL
Relay application	Remote control
Poles description	2P
Pole contact composition	1 C/O + 1 NO
[In] rated current	16 A
Network type	AC

## Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	250 V AC 50/60 Hz
Control type	Remote control Toggle
Control signal type	Impulse
Switching frequency	5 switching operations/minute
Impulse duration	50 ms
Remote control type	Illuminated push-button 3 mA
Local signalling	ON/OFF indication
[Uc] control circuit voltage	230...240 V AC 50/60 Hz 110 V DC
Supply inrush power	19 VA
Mounting mode	Fixed, on right side of TL
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	84 mm
Width	18 mm
Depth	60 mm
Colour	Grey
Electrical durability	AC-21: 200000 cycles AC-22: 100000 cycles

<b>Connections - terminals</b>	Tunnel type terminals - $\leq 10 \text{ mm}^2$
<b>Auxiliary connection terminal</b>	Tunnel type terminals control circuit in 0.5...6 mm <sup>2</sup>

## Environment

<b>Standards</b>	EN 60947-1 EN 60947-2-2
<b>Product certifications</b>	GOST VDE CEBEC IMQ NF
<b>Noise level</b>	60 dB
<b>Tropicalisation</b>	2
<b>Relative humidity</b>	95 % at 55 °C
<b>Ambient air temperature for operation</b>	-20...50 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	8 cm
<b>Package 1 Width</b>	3 cm
<b>Package 1 Length</b>	8.5 cm
<b>Package 1 Weight</b>	0.124 kg

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Recommended replacement(s)

15530 is replaced by:

1x



extension iETL iTL 16- 2P - 1C/O+1NO -16A - coil 110VDC - 230...240V AC 50/60Hz  
A9C32816