

Electrical parts availability

Standard Coil Mono-Frequency, F class

Encapsulated in synthetic material, Connector for 2P + E DIN 43650 A Plug, IP65 rate can be achieved using a DIN Plug connector only.

Voltage	Power Consumption	Approvals	Description	Part Number	Dimensional Drawing
24/50	8 W	-	481865A2	430500	10
48/50	8 W	-	481865A4	430515	10
110/50	8 W	-	481865A5	430514	10
220-230/50	8 W	-	481865B0	430502	10
300/50	8 W	-	481865A9	430531	10
24/60	8 W	-	481865B2	430504	10
230/60	8 W	-	481865J3	430530	10
115/60	8 W	-	481865B3	430528	10
12 DC	9 W	-	481865C1	430508	10
24 DC	9 W	-	481865C2	430501	10
48DC	9 W	-	481865C4	430523	10
110V DC	9 W	-	481865C5	430532	10

Standard Coil Bi-Frequency, F class

Encapsulated in synthetic material, Connector for 2P + E DIN 43650 A Plug, IP65 rate can be achieved using a DIN Plug connector only.

Voltage	Power Consumption	Approvals	Description	Part Number	Dimensional Drawing
12/50-60	9 W	-	4835101W	430512	10
24/50-60	9 W	-	483510P0	430503	10
48/50-60	9 W	-	483510S4	430526	10
110-115/50-120/60	9 W	-	483510S5	430507	10
220-240/50-240/60	9 W	-	483510S6	430504	10

UL approved Coil, F class

Encapsulated in synthetic material, Connector for 2P + E DIN 43650 A Plug, IP65 rate can be achieved using a DIN Plug connector only.

Voltage	Power Consumption	Approvals	Description	Part Number	Dimensional Drawing
24/60	12 W	UL	491514B2	430511	10
24DC	16 W	UL, ADF	491514C2	430520	10
110/50-120/60	12 W	UL	491514F3	430512	10
220/50-240/60	12 W	UL	491514Q3	430513	10

H class Coil

(DC, AC 14W) encapsulated in synthetic material. Connection for 2P + E DIN 43650 A Plug, IP65 rate can be achieved using a DIN Plug connector only.

Voltage	Power Consumption	Approvals	Description	Part Number	Dimensional Drawing
24/50	14 W	-	492425A2	430550	10
110/50	14 W	-	492425A5	430551	10
230/50	14 W	-	492425F4	430518	10
24DC	14 W	-	492425C2	430522	10