

(!) Discontinued

die-cast empty control station - XAPM - Ø 22 - zinc alloy - 2 openings

XAPM2502H29

- ! Discontinued on: 2 Nov 2022
- ! End-of-service on: 30 Jun 2025

Main

Range of product	Harmony XAP						
Product or component type	Die-cast empty control station						
Device short name	XAPM						
Product destination	For Ø 22 mm control and signalling units						
Product front plate size	80 x 130 mm						
Usable depth	74.5 mm						
Number of cut-out	2 cut-outs						
Colour of base of enclosure	Blue						
Colour of cover	Blue						
Material	Zinc alloy						
Cable entry	1 hole with blanking plug for ISO 429248 cable gland, clamping capacity: 20 mm 1 hole without blanking plug for ISO 429248 cable gland, clamping capacity: 20 mm						
Device mounting	Flush						
IP degree of protection	IP65 conforming to IEC 60529 IP69 conforming to NF C 20-010 IP69K						

Complementary

Number of vertical rows	1
Net weight	0.81 kg

Environment

Protective treatment	TC
Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	-4070 °C
Overvoltage category	Class I conforming to IEC 60536 Class I conforming to NF C 20-030

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.3 cm

Package 1 Width	8.8 cm			
Package 1 Length	15.5 cm			
Package 1 Weight	1 006 ka			

Contractual warranty

Warranty (in months)

18



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

0	Environmental	factorist
~	Environmental	100tbi iiit

Environmental Disclosure

Product Environmental Profile

Use Better


Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)

Use Again

○ Repack and remanufacture	
End of life manual availability	No need of specific recycling operations

Dimensions Drawings

Dimensions and Fixing



- (1) 1 hole, without blanking plug, for cable gland with 14 mm/0.55 in. maximum clamping capacity
- (2) 1 hole, with blanking plug (protrusion 6 mm/0.23 in.), for cable gland with 14 mm/0.55 in. maximum clamping capacity
- (3) $2 \times \emptyset$ 5.6 mm/0.22 in. holes, depth 20 mm/0.78 in.
- P Usable depth

a b		c		G		Н		P			
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.
80	3.15	130	5.12	77	3.03	50	1.97	155	4.53	74.5	2.93

Refer to the product characteristics to get the number of cut-outs.

Cut-out interaxis dimensions




b1 Vertical interaxis: 40 mm/1.57 in.

XAPM2502H29

Technical Illustration

Dimensions



- (1) 1 hole (no plug) for cable gland, max clamp Ø14 mm / 0.55 in. (2) 1 hole (with plug, 6 mm / 0.23 in. protrusion) for cable gland, max clamp Ø14 mm / 0.55 in. (3) 2 holes Ø5.6 mm / 0.22 in., depth 20 mm / 0.78 in.

Cut-out interaxis



Image of product / Alternate images

Alternative









