

Harmony XAP, XB2 SL, Empty control station, zinc alloy, blue, 6 cut-outs, 22mm, 80 x 175 x 77 mm

XAPM3506

! Discontinued on: Aug 30, 2022

① Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Range of Product	Harmony XAP						
Product or Component Type	Die-cast empty control station						
Device short name	XAPM						
Product destination	For Ø 22 mm control and signalling units						
Product front plate size	80 x 175 mm						
Usable depth	2.9 in (74.5 mm)						
Number of cut-out	6 cut-outs						
Colour of base of enclosure	Blue						
Colour of cover	Blue						
Material	Zinc alloy						
Cable entry	1 hole with blanking plug for cable gland 0.7 in (18 mm) 1 hole without blanking plug for cable gland 0.7 in (18 mm)						
Device mounting	Flush						
IP degree of protection	IP65 IEC 60529						

## Complementary

Number of vertical rows	2
Product Weight	2.49 lb(US) (1.13 kg)

# **Environment**

Protective treatment	TC
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient Air Temperature for Operation	-40158 °F (-4070 °C)
Overvoltage category	Class I conforming to IEC 60536 Class I conforming to NF C 20-030

# Ordering and shipping details

Category	US10CS222475
Discount Schedule	0CS2
GTIN	3389110312966
Returnability	No

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

# **Packing Units**

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.35 in (8.5 cm)
Package 1 Width	4.72 in (12 cm)
Package 1 Length	7.36 in (18.7 cm)
Package weight(Lbs)	2.846 lb(US) (1.291 kg)

# **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

# ∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

#### **Use Better**


EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations

#### **Dimensions Drawings**

#### **Dimensions and Fixing**




- (1) 1 hole, without blanking plug, for cable gland with 18 mm/0.71 in. maximum clamping capacity
- (2) 1 hole, with blanking plug (protrusion 6 mm/0.23 in.), for cable gland with 18 mm/0.71 in. maximum clamping capacity
- (3)  $2 \times \emptyset$  5.6 mm/0.22 in. holes, depth 20 mm/0.78 in.
- P Usable depth

а		b		c		G		Н		P	
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.
80	3.15	175	6.89	77	3.03	50	1.97	160	6.30	74.5	2.93

Refer to the product characteristics to get the number of cut-outs.

Cut-out interaxis dimensions (vertical mounting)



- b1 Vertical interaxis: 40 mm/1.57 in.
- b2 Horizontal interaxis: 30 mm/1.18 in.

Image of product / Alternate images

### **Alternative**











