

# Product data sheet

Specifications



## Complete joystick controller, Harmony XK, XKBA, 2 movements, 4 directions

XKBA31207

⚠ Discontinued on: Jan 23, 2023

⚠ Discontinued

**Product availability: Non-Stock - Not normally stocked in distribution facility**

### Main

Range Of Product	Harmony XK
Product Or Component Type	Complete joystick controller
Product Specific Application	Light hoisting applications

### Complementary

Device Short Name	XKB
Bezel Material	Metal
Fixing Collar Material	Metal
Sale Per Indivisible Quantity	1
Protective Treatment	TC
Ambient Air Temperature For Storage	-40...158 °F (-40...70 °C)
Ambient Air Temperature For Operation	-4...158 °F (-20...70 °C)
Overvoltage Category	Class I IEC 61140
Ip Degree Of Protection	IP54 IEC 60529 IP20 IEC 60529
Standards	CSA C22.2 No 14 UL 508 EN/IEC 60947-5-1
Product Certifications	CCC CSA RRS UL
Contact Code Designation	A300 Q300
Operator Position Information	All positions
Operator Profile	Handle with zero position mechanical interlock
Notch Per Direction	1...3 12°-20°-28° for each direction
Mechanical Durability	1000000 cycles
Vibration Resistance	2 gn 10...500 Hz IEC 60068-2-6
Shock Resistance	15 gn 11 ms) IEC 60068-2-27
Connections - Terminals	Captive screw clamp terminals, <= 2 x 1.5 mm <sup>2</sup> with cable end Captive screw clamp terminals, <= 1 x 2.5 mm <sup>2</sup> without cable end Captive screw clamp terminals, >= 1 x 0.5 mm <sup>2</sup>
Short-Circuit Protection	10 A cartridge fuse gG EN/IEC 60947-5-1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

<b>[Ith] Conventional Free Air Thermal Current</b>	10 A EN/IEC 60947-5-1 10 A CSA C22.2 No 14 10 A UL 508
--	--

---

<b>[Ui] Rated Insulation Voltage</b>	500 V 3)IEC 60947-1
--------------------------------------	---------------------

---

## Ordering and shipping details

---

<b>Category</b>	US1000I22474
-----------------	--------------

---

<b>Discount Schedule</b>	000I
--------------------------	------

---

<b>Gtin</b>	785901145349
-------------	--------------

---

<b>Returnability</b>	No
----------------------	----

---

<b>Country Of Origin</b>	FR
--------------------------	----

---

## Packing Units

---

<b>Unit Type Of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number Of Units In Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	9.50 in (24.13 cm)
-------------------------	--------------------

---

<b>Package 1 Width</b>	6.50 in (16.51 cm)
------------------------	--------------------

---

<b>Package 1 Length</b>	6.00 in (15.24 cm)
-------------------------	--------------------

---

<b>Package 1 Weight</b>	16.00 oz (453.592 g)
-------------------------	----------------------

---

## Contractual warranty

---

<b>Warranty</b>	18 months
-----------------	-----------

---

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

## Well-being performance

 Mercury Free

---

 Rohs Exemption Information [Yes](#)

---

**Reach Regulation** [REACH Declaration](#)

---

**Eu Rohs Directive** Pro-active compliance (Product out of EU RoHS legal scope)

---

**China Rohs Regulation** [China RoHS declaration](#)

---