

Product datasheet

Specifications



joystick controller XKDF for medium hoisting applications

XKDF11340340

⚠ Discontinued on: 31 Oct 2022

Price: 24,550.88 ZAR

⚠ Discontinued

Main

Range Of Product	Harmony XK
Product Or Component Type	Complete joystick controller
Product Specific Application	Light hoisting applications

Complementary

Device Short Name	XKB
Bezel Material	Metal
Fixing Collar Material	Metal
Sale Per Indivisible Quantity	1
Protective Treatment	TC
Ambient Air Temperature For Storage	-40...70 °C
Ambient Air Temperature For Operation	-20...70 °C
Overvoltage Category	Class I conforming to IEC 61140
Ip Degree Of Protection	IP54 conforming to IEC 60529 IP20 conforming to IEC 60529
Standards	CSA C22.2 No 14 EN/IEC 60947-5-1
Product Certifications	CSA UL CCC RRS
Contact Code Designation	Q300 A300
Operator Position Information	All positions
Operator Profile	Handle with zero position mechanical interlock
Notch Per Direction	1...5 notches at 12°-18°-24°-30°-36° for each direction 1...3 notches at 12°-24°-36° for each direction
Mechanical Durability	1000000 cycles
Vibration Resistance	2 gn (f= 10...500 Hz) conforming to IEC 60068-2-6
Shock Resistance	15 gn (duration = 11 ms) conforming to IEC 60068-2-27
Short-Circuit Protection	10 A cartridge fuse type gG conforming to EN/IEC 60947-5-1
[Ith] Conventional Free Air Thermal Current	10 A conforming to EN/IEC 60947-5-1 10 A conforming to CSA C22.2 No 14
[Ui] Rated Insulation Voltage	500 V (pollution degree 3) conforming to IEC 60947-1

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

