

Product datasheet

Specifications



thermal overload relay for motor - TeSys LR.D - 63...80 A - class 10A

LR2D3363

EAN Code: 3389110232981

! Discontinued

Main

Range Of Product	TeSys D
Device Short Name	LR2D
Product Or Component Type	Thermal overload relay
Relay Application	Motor protection
Product Compatibility	LE4D656
Protection Type	BS fuse 5 A - for control circuit GB2 circuit breaker 5 A - for control circuit GG fuse 5 A - for control circuit
Connections - Terminals	Control circuit: screw clamp terminals 1 x 1...2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 x 1...2.5 mm ² flexible without cable end Control circuit: screw clamp terminals 2 x 1...2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 2 x 1...2.5 mm ² flexible without cable end Control circuit: screw clamp terminals 2 x 1...2.5 mm ² solid without cable end
Quantity Per Set	Set of 10

Complementary

Network Frequency	50/60 Hz
Mounting Support	Plate, with EverLink power terminal block Rail, with EverLink power terminal block
Tripping Threshold	1.14 +/-0.06 In A conforming to IEC 60947-4-1
Surge Withstand	6 kV conforming to IEC 60801-5
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz for power circuit conforming to IEC 60947-4-1
Phase Failure Sensitivity	Tripping current I 30 % of I _r on one phase, the others at I _r conforming to IEC 60947-4-1
Tightening Torque	Control circuit: 1.7 N.m on screw clamp terminals
Height	121 mm
Width	75 mm
Depth	100 mm

Environment

Standards	IEC 60947-4-1 UL 508 IEC 60947-5-1 CSA C22.2 No 14 Directive ATEX 94/9/EC EN 60947-4-1 EN 60947-5-1
-----------	---

Product Certifications	RINA LROS (Lloyds register of shipping) DNV CSA GL UL ATEX INERIS BV GOST CCC
Protective Treatment	TH conforming to IEC 60068
Ip Degree Of Protection	IP2X conforming to VDE 0106
Ambient Air Temperature For Operation	-20...60 °C conforming to IEC 60947-4-1
Fire Resistance	850 °C conforming to IEC 60695-2-1
Shock Resistance	15 gn 11 ms conforming to IEC 60068-2-7
Vibration Resistance	6 gn on plate conforming to IEC 60068-2-6
Dielectric Strength	6 kV 50 Hz conforming to IEC 60255-5

Contractual warranty

Warranty	18 months
-----------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Certifications & Standards

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)