

# Product datasheet

Specifications



## discrete input module Twido - 8 inputs - 24 V DC

TWDDDI8DT

⚠ Discontinued on: 31 Dec 2016

⚠ End-of-service on: 31 Dec 2021

⚠ Discontinued

EAN Code: 3595862043649

### Main

Range Of Product	Twido
Product Or Component Type	Discrete input module
Discrete Input Number	8
Discrete Input Voltage	24 V
Discrete Input Voltage Type	DC
I/O Connection	Removable screw terminal block
Number Of Common Point	1

### Complementary

Input Voltage Limits	20.4...28.8 V
Discrete Input Logic	Sink or source
Discrete Input Current	7 mA
Input Impedance	3.4 kOhm
Filter Time	8 ms at state 0 8 ms at state 1
Insulation Between Channel And Internal Logic	1500 Vrms for 1 min (by photocoupler)
Current Consumption	25 mA at 5 V DC at state 1 for all inputs 5 mA at 5 V DC at state 0 for all inputs
Marking	CE
Terminals Description Plc N°1	(8)COM_POS (7)IN_DIS#7 (5)IN_DIS#5 (0)IN_DIS#0 (3)IN_DIS#3 (1)IN_DIS#1 ALT (9)COM_POS (2)IN_DIS#2 (4)IN_DIS#4 (6)IN_DIS#6
Terminals Description Plc N°2	(9)COM#1-8 (5)IN_DIS#5 (7)IN_DIS#7 (8)COM_NEG (1)IN_DIS#1 (2)IN_DIS#2 (0)IN_DIS#0 (3)IN_DIS#3 ALT_1 (4)IN_DIS#4 (6)IN_DIS#6

---

Net Weight	0.085 kg
------------	----------

## Environment

---

Product Certifications	UL CSA
------------------------	-----------

---

Ip Degree Of Protection	IP20
-------------------------	------

---

Ambient Air Temperature For Operation	0...55 °C
---------------------------------------	-----------

---

Ambient Air Temperature For Storage	-25...70 °C
-------------------------------------	-------------

---

## Contractual warranty

---

Warranty	18 months
----------	-----------