Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

TeSys F - contactor coil - LX1FH -110...115 V AC 40...400 Hz

Local distributor code: 380914010

LX1FH1102

! Discontinued on: 29 Sept 2023

EAN Code: 3389110553345

! To be discontinued

Main

Range	TeSys	
Product or component type	Contactor coil	
Device short name	LX1FH	
Range compatibility	TeSys TeSys F LC1F contactor	
Product compatibility	LC1F330 LC1F265	
Control circuit type	AC at 40400 Hz	
[Uc] control circuit voltage	110115 V AC 40400 Hz	
Average resistance	18.7 Ohm inrush at 20 °C 440 Ohm holding at 20 °C	
Operating time	100170 ms opening 4065 ms closing	
Mechanical durability	10 Mcycles	
Maximum operating rate	2400 cyc/h 55 °C	

Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits	Drop-out: 0.350.55 Uc 40400 Hz (at 55 °C) Operational: 0.851.1 Uc 40400 Hz (at 55 °C)	
Inrush power in VA	650 VA 40400 Hz cos phi 0.9 (at 20 °C)	
Hold-in power consumption in VA	10 VA 40400 Hz cos phi 0.3 (at 20 °C)	
Heat dissipation	8 W at 40400 Hz	

Environment

Ambient air temperature for operation	-555 °C
Net weight	0.75 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.200 cm
Package 1 Width	11.000 cm
Package 1 Length	19.400 cm

Package 1 Weight	865.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	10.818 kg
Unit Type of Package 3	P06
Number of Units in Package 3	96
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	97.436 ka

Logistical informations

Country of origin CZ

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

Environmental Disclosure Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No