Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



TeSys F - contactor coil - LX1FL -110...120 V AC 40...400 Hz

Local distributor code: 2200646

LX1FL110

! Discontinued on: 29 Sept 2023

EAN Code: 3389110082401

① To be discontinued

Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX1FL
Range compatibility	TeSys TeSys F LC1F contactor
Product compatibility	LC1F1250 LC1F630
Control circuit type	AC at 40400 Hz
[Uc] control circuit voltage	110120 V AC 40400 Hz
Inductance of closed circuit	1.85 H
Average resistance	6.45 Ohm inrush at 20 °C 165 Ohm holding at 20 °C
Operating time	100200 ms opening 4080 ms closing
Mechanical durability	5 Mcycles
Maximum operating rate	1200 cyc/h 55 °C

Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits	Operational: 0.851.1 Uc 40400 Hz (at 55 °C) Drop-out: 0.250.5 Uc 40400 Hz (at 55 °C)	
Inrush power in VA	1650 VA 40400 Hz cos phi 0.9 (at 20 °C)	
Hold-in power consumption in VA	22 VA 40400 Hz cos phi 0.3 (at 20 °C)	
Heat dissipation	20 W at 40400 Hz	

Environment

ambient air temperature for operation	-555 °C
Net weight	1.5 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.0 cm
Package 1 Width	12.0 cm

Package 1 Length	22.5 cm
Package 1 Weight	1.466 kg
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	9.21 kg

Logistical informations

Country of origin CZ

Contractual warranty

Warranty 18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
EU RoHS Directive REACh Regulation	(Product out of EU RoHS legal

Use Again

Circularity Profile	End of Life Information
Take-back	No