

Product data sheet

Specifications



Auxiliary contacts, TeSys GS, 1 C/O, early break, front mounting, for GS1 50 to 400A with direct right handle

GS1AM1

Discontinued

Discontinued on: May 5, 2023

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	TeSys
Device short name	GS1AM1
Product or Component Type	Auxiliary contact
Contact application	O and I position signalling
Range compatibility	TeSys TeSys GS GS1 F fuse-switch disconnecter TeSys TeSys GS GS1G fuse-switch disconnecter TeSys TeSys GS GS1 J fuse-switch disconnecter TeSys TeSys GS GS1 K fuse-switch disconnecter TeSys TeSys GS GS1 L fuse-switch disconnecter TeSys TeSys GS GS1 N fuse-switch disconnecter TeSys TeSys GS GS1Q fuse-switch disconnecter
Contacts type and composition	1 C/O
Contact operation	Early-break
[I _{th}] conventional free air thermal current	16 A (at 104.000000000 °F (40 °C))
[I _e] rated operational current	5 A 127 V AC-15 4 A 230 V AC-15 3 A 400/415 V AC-15 2 A 440 V AC-15 12 A 24 V DC-13 2 A 48 V DC-13 0.6 A 110 V DC-13 0.4 A 220 V DC-13

Complementary

Mechanical durability	1 Mcycles
Electrical durability	30000 cycles AC-15
switch rated current	50 A 63 A 100 A 125 A 160 A 200 A 250 A 315 A 400 A
Fuse type	NFC DIN BS
Type of operating handle	Direct right side
mounting location	Front face

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Net Weight	0.051 lb(US) (0.023 kg)
------------	-------------------------

Ordering and shipping details

Category	US1CP1018402
----------	--------------

Discount Schedule	CP10
-------------------	------

GTIN	3389110563214
------	---------------

Returnability	No
---------------	----

Country of origin	FR
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	1.0 in (2.5 cm)
------------------	-----------------

Package 1 Width	3.7 in (9.5 cm)
-----------------	-----------------

Package 1 Length	4.3 in (11.0 cm)
------------------	------------------

Package 1 Weight	0.8 oz (24.0 g)
------------------	-----------------

Unit Type of Package 2	S02
------------------------	-----

Number of Units in Package 2	60
------------------------------	----

Package 2 Height	5.9 in (15.0 cm)
------------------	------------------

Package 2 Width	11.8 in (30.0 cm)
-----------------	-------------------

Package 2 Length	15.7 in (40.0 cm)
------------------	-------------------

Package 2 Weight	4.178 lb(US) (1.895 kg)
------------------	-------------------------

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Eu Rohs Directive [Compliant](#)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)

California Proposition 65 **WARNING:** This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov